


Polygon Mesh Data Structure for 3D Graphics


Introduction

The polygon mesh data structure is the most common and oldest modeling method for computer graphics.

Here is a wireframe teapot.



Here is a pen and ink drawing of a wireframe chalice ("Perspective Study of a Chalice"), done by Paolo Uccello in 1430-1440, Florence, Italy.



PCL XL error

Subsystem: KERNEL

Error: IllegalOperatorSequence

Operator: SetColorSpace

Position: 534


[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Search Results

Search Results for: [(polygon or mesh) <sentence> (face or patch) <sentence> path]

Found 23 of 119,560 searched.

Search within Results


[> Advanced Search](#) [> Search Help/Tips](#)
Sort by: [Title](#) [Publication](#) [Publication Date](#) [Score](#) [Binder](#)Results 1 - 20 of 23 [short listing](#)

[Prev Page](#)
[1](#)
[2](#)
[Next Page](#)

- 1 [Structured visibility profiles with applications to problems in simple polygons \(extended abstract\)](#) 100%

Paul J. Heffernan , Joseph S. B. Mitchell

Proceedings of the sixth annual symposium on Computational geometry May 1990

A number of problems in computational geometry involving simple polygons can be solved in linear time once the polygon has been triangulated. Since the worst-case time bound for triangulating a general simple polygon is currently super-linear, these algorithms are not linear time in the worst case. In this paper we define the structured visibility profile of a polygonal path and show how to compute it in linear time. We apply this result to solve many problems in linear time ...

- 2 [Detection of constrictions on closed polyhedral surfaces](#) 100%

F. Hétroy , D. Attali

Proceedings of the symposium on Data visualisation 2003 May 2003

We define constrictions on a surface as simple closed geodesic curves, i.e. curves whose length is locally minimal. They can be of great interests in order to cut the surface in smaller parts. In this paper, we present a method to detect constrictions on closed triangulated surfaces. Our algorithm is based on a progressive approach. First, the surface is simplified by repeated edge collapses. The simplification continues until we detect an edge whose collapse would change the topology of the surface ...

- 3 [Path planning in 0/1/ weighted regions with applications](#) 100%

L. Gewali , A. Meng , J. S. Mitchell , S. Ntafos

Proceedings of the fourth annual symposium on Computational geometry January 1988

We consider the terrain navigation problem in a two-dimensional polygonal subdivision consisting of obstacles, "free" regions (in which one can travel at no cost), and regions in which cost is proportional to distance traveled. This problem is a special case of the weighted region problem and is a generalization of the well-known planar shortest path problem

09/515, 517

[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Citation

International Conference on Computer Graphics and Interactive Techniques >archive
Proceedings of the 24th annual conference on Computer graphics and interactive techniques >toc
1997 ,

Interactive multiresolution mesh editing

Authors

Denis Zorin

Peter Schröder

Wim Sweldens

Sponsor

SIGGRAPH : ACM Special Interest Group on Computer Graphics and Interactive Techniques

Publisher

ACM Press/Addison-Wesley Publishing Co. New York, NY, USA

Pages: 259 - 268 Series-Proceeding-Article

Year of Publication: 1997

ISBN:0-89791-896-7

<http://doi.acm.org/10.1145/258734.258863> (Use this link to Bookmark this page)

[> full text](#) [> references](#) [> citings](#) [> peer to peer](#)

[> Discuss](#)

[> Similar](#)

[> Review this Article](#)

[Save to Binder](#)

[> BibTex Format](#)

↑ FULL TEXT: [Access Rules](#)

pdf 10.63 MB

↑ REFERENCES

Note: OCR errors may be found in this Reference List extracted from the full text article. ACM has opted to expose the complete List rather than only correct and linked references.

1 BURT, P. J., AND ADELSON, E. H. Laplacian Pyramid as a Compact Image Code. IEEE Trans. Commun. 31, 4 (1983), 532-540.

- 2 CATMULL, E., AND CLARK, J. Recursively Generated B- Spline Surfaces on Arbitrary Topological Meshes. *Computer Aided Design* 10, 6 (1978), 350-355.
- 3 Andrew Certain , Jovan Popovic , Tony DeRose , Tom Duchamp , David Salesin , Werner Stuetzle, Interactive multiresolution surface viewing, Proceedings of the 23rd annual conference on Computer graphics and interactive techniques, p.91-98, August 1996
- 4 DAHMEN, W., MICCHELLI, C. A., AND SEIDEL, H.- P. Blossoming Begets B-Splines Bases Built Better by B- Patches. *Mathematics of Computation* 59, 199 (July 1992), 97-115.
- 5 DE BOOR, C. A Practical Guide to Splines. Springer, 1978.
- 6 Doo, D., AND S ABIN, M. Analysis of the Behaviour of Recursive Division Surfaces near Extraordinary Points. *Computer Aided Design* 10, 6 (1978), 356-360.
- 7 Nira Dyn , David Levine , John A. Gregory, A butterfly subdivision scheme for surface interpolation with tension control, ACM Transactions on Graphics (TOG), v.9 n.2, p.160-169, April 1990
- 8 Matthias Eck , Tony DeRose , Tom Duchamp , Hugues Hoppe , Michael Lounsbery , Werner Stuetzle, Multiresolution analysis of arbitrary meshes, Proceedings of the 22nd annual conference on Computer graphics and interactive techniques, p.173-182, September 1995
- 9 Adam Finkelstein , David H. Salesin, Multiresolution curves, Proceedings of the 21st annual conference on Computer graphics and interactive techniques, p.261-268, July 1994
- 10 FORSEY, D., AND WONG, D. Multiresolution Surface Reconstruction for Hierarchical B-splines. Tech. rep., University of British Columbia, 1995.
- 11 FORSEY, D. R., AND BARTELS, R. H. Hierarchical B-Spline Refinement. *Computer Graphics (SIGGRAPH '88 Proceedings)*, Vol. 22, No. 4, pp. 205-212, August 1988.
- 12 Steven J. Gortler , Michael F. Cohen, Hierarchical and variational geometric modeling with wavelets, Proceedings of the 1995 symposium on Interactive 3D graphics, p.35-ff., April 09-12, 1995, Monterey, California, United States
- 13 Hugues Hoppe, Progressive meshes, Proceedings of the 23rd annual conference on Computer graphics and interactive techniques, p.99-108, August 1996
- 14 Hugues Hoppe , Tony DeRose , Tom Duchamp , Mark Halstead , Hubert Jin , John McDonald , Jean Schweitzer , Werner Stuetzle, Piecewise smooth surface reconstruction, Proceedings of the 21st annual conference on Computer graphics and interactive techniques, p.295-302, July 1994
- 15 Hugues Hoppe , Tony DeRose , Tom Duchamp , John McDonald , Werner Stuetzle, Mesh optimization, Proceedings of the 20th annual conference on Computer graphics and interactive techniques, p.19-26, September 1993
- 16 KOBBELT, L. Interpolatory Subdivision on Open Quadrilateral Nets with Arbitrary Topology. In *Proceedings of Eurographics 96, Computer Graphics Forum*, 409-420, 1996.
- 17 Venkat Krishnamurthy , Marc Levoy, Fitting smooth surfaces to dense polygon meshes, Proceedings

of the 23rd annual conference on Computer graphics and interactive techniques, p.313-324, August 1996

18 KURIHARA, T. Interactive Surface Design Using Recursive Subdivision. In Proceedings of Communicating with Virtual Worlds. Springer Verlag, June 1993.

19 LooP, C. Smooth Subdivision Surfaces Based on Triangles. Master's thesis, University of Utah, Department of Mathematics, 1987.

20 Charles Loop, Smooth spline surfaces over irregular meshes, Proceedings of the 21st annual conference on Computer graphics and interactive techniques, p.303-310, July 1994

21 Michael Lounsbery , Tony D. DeRose , Joe Warren, Multiresolution analysis for surfaces of arbitrary topological type, ACM Transactions on Graphics (TOG), v.16 n.1, p.34-73, Jan. 1997

22 Jörg Peters, C1-surface splines, SIAM Journal on Numerical Analysis, v.32 n.2, p.645-666, April 1995

23 PULLI, K., AND LOUNSBERY, M. Hierarchical Editing and Rendering of Subdivision Surfaces. Tech. Rep. UW-CSE- 97-04-07, Dept. of CS&E, University of Washington, Seattle, WA, 1997.

24 Peter Schröder , Wim Sweldens, Spherical wavelets: efficiently representing functions on the sphere, Proceedings of the 22nd annual conference on Computer graphics and interactive techniques, p.161-172, September 1995

25 SCHWEITZER, J. E. Analysis and Application of Subdivision Surfaces. PhD thesis, University of Washington, 1996.

26 Gabriel Taubin, A signal processing approach to fair surface design, Proceedings of the 22nd annual conference on Computer graphics and interactive techniques, p.351-358, September 1995

27 William Welch , Andrew Witkin, Variational surface modeling, ACM SIGGRAPH Computer Graphics, v.26 n.2, p.157-166, July 1992

28 Denis Zorin , Peter Schröder , Wim Sweldens, Interpolating Subdivision for meshes with arbitrary topology, Proceedings of the 23rd annual conference on Computer graphics and interactive techniques, p.189-192, August 1996

29 ZORIN, D. N. Subdivision and Multiresolution Surface Representations. PhD thesis, Caltech, Pasadena, California, 1997.

↑ CITINGS 31

Frederick W. B. Li , Rynson W. H. Lau, Real-time rendering of deformable parametric free-form surfaces, Proceedings of the ACM symposium on Virtual reality software and technology, p.131-138, December 20-22, 1999, London, United Kingdom

Xinguo Liu , Hujun Bao , Heung-Yeung Shum , Qunsheng Peng, A novel volume constrained smoothing method for meshes, Graphical Models, v.64 n.3/4, p.169-182, May/July 2002

Nathan Litke , Adi Levin , Peter Schröder, Fitting subdivision surfaces, Proceedings of the conference on

Visualization 2001, October 21-26, 2001, San Diego, California

Gabriel Taubin, Is this a quadrisected mesh?, Proceedings of the sixth ACM symposium on Solid modeling and applications, p.261-266, May 2001, Ann Arbor, Michigan, United States

Holger Grahn , Thomas Volk , Hans J. Wolters, NURBS in VRML, Proceedings of the fifth symposium on Virtual reality modeling language (Web3D-VRML), p.35-43, February 20-24, 2000, Monterey, California, United States

Jeffrey Bolz , Peter Schröder, Rapid evaluation of Catmull-Clark subdivision surfaces, Proceeding of the seventh international conference on 3D Web technology, p.11-17, February 24-28, 2002, Tempe, Arizona, USA

Andreas Hubeli , Markus Gross, Multiresolution feature extraction for unstructured meshes, Proceedings of the conference on Visualization 2001, October 21-26, 2001, San Diego, California

Carlos Gonzalez-Ochoa , Jorg Peters, Localized-hierarchy surface splines (LeSS), Proceedings of the 1999 symposium on Interactive 3D graphics, p.7-15, April 26-29, 1999, Atlanta, Georgia, United States

Gabriel Taubin , André Guézic , William Horn , Francis Lazarus, Progressive forest split compression, Proceedings of the 25th annual conference on Computer graphics and interactive techniques, p.123-132, July 1998

Daniel I. Azuma , Daniel N. Wood , Brian Curless , Tom Duchamp , David H. Salesin , Werner Stuetzle, View-dependent refinement of multiresolution meshes with subdivision connectivity, Proceedings of the 2nd international conference on Computer graphics, virtual Reality, visualisation and interaction in Africa, February 03-05, 2003, Cape Town, South Africa

Xianfeng Gu , Steven J. Gortler , Hugues Hoppe, Geometry images, ACM Transactions on Graphics (TOG), v.21 n.3, July 2002

Igor Guskov , Kiril Vidim?e , Wim Sweldens , Peter Schröder, Normal meshes, Proceedings of the 27th annual conference on Computer graphics and interactive techniques, p.95-102, July 2000

Chandrajit L. Bajaj , Valerio Pascucci , Guozhong Zhuang, Progressive compressive and transmission of arbitrary triangular meshes, Proceedings of the conference on Visualization '99: celebrating ten years, p.307-316, October 1999, San Francisco, California, United States

Tim Milliron , Robert J. Jensen , Ronen Barzel , Adam Finkelstein, A framework for geometric warps and deformations, ACM Transactions on Graphics (TOG), v.21 n.1, p.20-51, January 2002

Jianbo Peng , Vasily Strela , Denis Zorin, A simple algorithm for surface denoising, Proceedings of the conference on Visualization 2001, October 21-26, 2001, San Diego, California

Lee Markosian , Jonathan M. Cohen , Thomas Crulli , John Hughes, Skin: a constructive approach to modeling free-form shapes, Proceedings of the 26th annual conference on Computer graphics and interactive techniques, p.393-400, July 1999

Aaron W. F. Lee , Wim Sweldens , Peter Schröder , Lawrence Cowsar , David Dobkin, MAPS: multiresolution adaptive parameterization of surfaces, Proceedings of the 25th annual conference on

Computer graphics and interactive techniques, p.95-104, July 1998

Jerome Edward Lengyel, Compression of time-dependent geometry, Proceedings of the 1999 symposium on Interactive 3D graphics, p.89-95, April 26-29, 1999, Atlanta, Georgia, United States

Igor Guskov , Wim Sweldens , Peter Schröder, Multiresolution signal processing for meshes, Proceedings of the 26th annual conference on Computer graphics and interactive techniques, p.325-334, July 1999

Leif Kobbelt, 3 -subdivision, Proceedings of the 27th annual conference on Computer graphics and interactive techniques, p.103-112, July 2000

Andrei Khodakovsky , Peter Schröder, Fine level feature editing for subdivision surfaces, Proceedings of the fifth ACM symposium on Solid modeling and applications, p.203-211, June 08-11, 1999, Ann Arbor, Michigan, United States

Kai Hormann , Ulf Labsik , Martin Meister , Gunther Greiner, Hierarchical extraction of iso-surfaces with semi-regular meshes, Proceedings of the seventh ACM symposium on Solid modeling and applications, June 17-21, 2002, Saarbrücken, Germany

Henrik Weimer , Joe Warren, Subdivision schemes for fluid flow, Proceedings of the 26th annual conference on Computer graphics and interactive techniques, p.111-120, July 1999

Leila De Floriani , Paola Magillo , Enrico Puppo , Davide Sobrero, A multi-resolution topological representation for non-manifold meshes, Proceedings of the seventh ACM symposium on Solid modeling and applications, June 17-21, 2002, Saarbrücken, Germany

Frutuoso G. M. Silva , Abel J. P. Gomes, Adjacency and incidence framework: a data structure for efficient and fast management of multiresolution meshes, Proceedings of the 1st international conference on Computer graphics and interactive techniques in Australasia and South East Asia, February 11-14, 2003, Melbourne, Australia

Aaron Lee , Henry Moreton , Hugues Hoppe, Displaced subdivision surfaces, Proceedings of the 27th annual conference on Computer graphics and interactive techniques, p.85-94, July 2000

Leif Kobbelt , Swen Campagna , Jens Vorsatz , Hans-Peter Seidel, Interactive multi-resolution modeling on arbitrary meshes, Proceedings of the 25th annual conference on Computer graphics and interactive techniques, p.105-114, July 1998

Henning Biemann , Ioana Martin , Fausto Bernardini , Denis Zorin, Cut-and-paste editing of multiresolution surfaces, ACM Transactions on Graphics (TOG), v.21 n.3, July 2002

↗ Peer to Peer - Readers of this Article have also read:

- Constructing reality
Proceedings of the 11th annual international conference on Systems documentation
Douglas A. Powell , Norman R. Ball , Mansel W. Griffiths
- Data structures for quadtree approximation and compression
Communications of the ACM 28, 9

Hanan Samet

- Toward a real-time Ada design methodology
Proceedings of the conference on TRI-ADA '90
Norman R. Howes
- Fashioning conceptual constructs in Ada
Proceedings of the conference on TRI-ADA '90
Robert C. Shock
- Reuse: the two concurrent life cycles paradigm
Proceedings of the conference on TRI-ADA '90
Richard Drake , William Ett

The ACM Portal is published by the Association for Computing Machinery. Copyright © 2003 ACM, Inc.

[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Search Results

Search Results for: [(polygon or mesh) and (face or patch) <near/2> ident*<AND>(((polygon or mesh) <sentence> (face or patch) <sentence> path))]

Found 1 of 119,560 searched.

Search within Results

[> Advanced Search](#) [> Search Help/Tips](#)

Sort by: [Title](#) [Publication](#) [Publication Date](#) [Score](#) [Binder](#)

Results 1 - 1 of 1 [short listing](#)

1 [Session P15: multidimensional, motion, and information visualization: A radial focus+context](#) 90%

[visualization for multi-dimensional functions](#)

Sanjini Jayaraman , Chris North

Proceedings of the conference on Visualization '02 October 2002

The analysis of multidimensional functions is important in many engineering disciplines, and poses a major problem as the number of dimensions increases. Previous visualization approaches focus on representing three or fewer dimensions at a time. This paper presents a new focus+context visualization that provides an integrated overview of an entire multidimensional function space, with uniform treatment of all dimensions. The overview is displayed with respect to a user-controlled polar focal po ...

Results 1 - 1 of 1 [short listing](#)

The ACM Portal is published by the Association for Computing Machinery. Copyright © 2003 ACM, Inc.

[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Search Results

Nothing Found

Your search for the *Phrase* **catmul** <near> **clark** did not return any results.

To search for *terms* separate them with **AND** or **OR**.

Click on the suggested options:

catmul AND <near> AND clark

catmul OR OR clark

To search for names try using only the last or first name.

You may revise it and try your search again below or click advanced search for more options.

catmul <near> clark	 
<input type="checkbox"/>	
<input type="button" value="SEARCH"/>	[Advanced Search] [Search Help/Tips]

[Complete Search Help and Tips](#)

The following characters have specialized meaning:

Special Characters	Description
, () [These characters end a text token.
= > < !	These characters end a text token because they signify the start of a field operator. (! is special: != ends a token.)
` @ \ Q < { [!	These characters signify the start of a delimited token. These are terminated by the end character associated with the start character.


[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Search Results

Search Results for: [(polygon or mesh) and data <near> structure and (face or patch)]
Found 2,419 of 119,560 searched.

Warning: Maximum result set of 200 exceeded. Consider refining.

Search within Results

Go

[> Advanced Search](#) [> Search Help/Tips](#)

Sort by: [Title](#) [Publication](#) [Publication Date](#) [Score](#)

Results 1 - 20 of 200 [short listing](#)



1

[2](#)[3](#)[4](#)[5](#)[6](#)[7](#)[8](#)[9](#)[10](#)

1 [Poster session: Feature preserving manifold mesh from an octree](#) 100%

Koji Ashida , Norman I. Badler

Proceedings of the eighth ACM symposium on Solid modeling and applications June 2003

We describe an algorithm to generate a manifold mesh from an octree while preserving surface features. The algorithm requires samples of a surface (coordinates) on the octree edges, along with the surface normals at those coordinates. The distinct features of the algorithm are:

- the output mesh is manifold,
- the resolution of the output mesh can be adjusted over the space with octree subdivision, and
- surface features are generally preserved.

A mesh generation algorit ...

2 [Session P12: meshes: Bounded-distortion piecewise mesh parameterization](#) 100%

Olga Sorkine , Daniel Cohen-Or , Rony Goldenthal , Dani Lischinski

Proceedings of the conference on Visualization '02 October 2002

Many computer graphics operations, such as texture mapping, 3D painting, remeshing, mesh compression, and digital geometry processing, require finding a low-distortion parameterization for irregular connectivity triangulations of arbitrary genus 2-manifolds. This paper presents a simple and fast method for computing parameterizations with strictly bounded distortion. The new method operates by flattening the mesh onto a region of the 2D plane. To comply with the distortion bound, the mesh is aut ...

3 [A novel FEM-based dynamic framework for subdivision surfaces](#) 100%


[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the **new** Portal design
Give us your opinion after using it.

Search Results

Search Results for: [(polygon or mesh) <sentence> (data <near> structure) and (face or patch) and level and path]

Found 116 of 119,560 searched.

Search within Results


[> Advanced Search](#) [> Search Help/Tips](#)

Sort by: [Title](#) [Publication](#) [Publication Date](#) [Score](#) [Binder](#)

Results 1 - 20 of 116 [short listing](#)



1

[2](#)[3](#)[4](#)[5](#)[6](#)

1 [Navigating through triangle meshes implemented as linear quadtrees](#)

97%

Michael Lee , Hanan Samet

ACM Transactions on Graphics (TOG) April 2000

Volume 19 Issue 2

Techniques are presented for navigating between adjacent triangles of greater or equal size in a hierarchical triangle mesh where the triangles are obtained by a recursive quadtree-like subdivision of the underlying space into four equilateral triangles. These techniques are useful in a number of applications, including finite element analysis, ray tracing, and the modeling of spherical data. The operations are implemented in a manner analogous to that used in a quadtree representation of d ...

2 [Ray shooting and other applications of spanning trees with low stabbing number](#)

90%

P. K. Agarwal

Proceedings of the fifth annual symposium on Computational geometry June 1989

In this paper we consider the following problem: Given a set @@@@ of n (possibly intersecting) line segments in the plane, preprocess them so that, given a query ray &rgr; emanating from a point p, we can quickly compute the intersection point &PHgr;(@@@@, &rgr;) of &rgr; with a segment of @@@@ that lies nearest to p. We present an algorithm that preprocesses @@@@, in time &Ogr;

3 [WYSIWYG NPR: drawing strokes directly on 3D models](#)

88%

Robert D. Kalnins , Lee Markosian , Barbara J. Meier , Michael A. Kowalski , Joseph C. Lee , Philip L. Davidson , Matthew Webb , John F. Hughes , Adam Finkelstein

ACM Transactions on Graphics (TOG), Proceedings of the 29th annual conference on Computer graphics and interactive techniques July 2002

Volume 21 Issue 3

We present a system that lets a designer directly annotate a 3D model with strokes, imparting a

[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Search Results


Search Results for: [(polygon or mesh) <sentence> (identif*) <near> (face or patch)]
Found 23 of 119,560 searched.

Search within Results

[> Advanced Search](#) [> Search Help/Tips](#)

Sort by: [Title](#) [Publication](#) [Publication Date](#) [Score](#) [Binder](#)

Results 1 - 20 of 23 [short listing](#)

**1** [Creating polyhedral stellations](#)

100%

Kathleen R. McKeown , Norman I. Badler

Proceedings of the 7th annual conference on Computer graphics and interactive techniques
July 1980

A process for creating and displaying stellations of a given polyhedral solid is described. A stellation is one of many star-like polyhedra which can be derived from a single solid by extending its existing faces. A program has been implemented which performs the stellation process on an input object and generates a 3-dimensional image of the stellated object on a computer graphics display screen. Pictures of icosahedron and rhombictriacontahedron stellations generated by the program are in ...

2 [Poster session: Feature preserving manifold mesh from an octree](#)

100%

Koji Ashida , Norman I. Badler

Proceedings of the eighth ACM symposium on Solid modeling and applications June 2003

We describe an algorithm to generate a manifold mesh from an octree while preserving surface features. The algorithm requires samples of a surface (coordinates) on the octree edges, along with the surface normals at those coordinates. The distinct features of the algorithm are:

- the output mesh is manifold,
- the resolution of the output mesh can be adjusted over the space with octree subdivision, and
- surface features are generally preserved.

A mesh generation algorit ...

3 [Applications of random sampling in computational geometry, II](#)

100%

K. L. Clarkson

Proceedings of the fourth annual symposium on Computational geometry January 1988

[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Search Results

Nothing Found

Your search for [(*) <AND>((lounsberry)<IN> author)] did not return any results.

You may revise it and try your search again below or click advanced search for more options.

(*) <AND>((lounsberry)<IN> author)	▲
<input type="checkbox"/>	▼
<input type="button" value="SEARCH"/> [Advanced Search] [Search Help/Tips]	

[Complete Search Help and Tips](#)

The following characters have specialized meaning:

Special Characters	Description
, () [These characters end a text token.
= > < !	These characters end a text token because they signify the start of a field operator. (! is special: != ends a token.)
` @ \ Q < { [!	These characters signify the start of a delimited token. These are terminated by the end character associated with the start character.


[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Search Results

Search Results for: **[(quadtree or octree) and data <near> structure and (face or patch) and (polygon or mesh)]**

Found 364 of 119,560 searched.

Warning: Maximum result set of 200 exceeded. Consider refining.

Search within Results


[> Advanced Search](#) [> Search Help/Tips](#)

Sort by: [Title](#) [Publication](#) [Publication Date](#) [Score](#)

Results 1 - 20 of 200 [short listing](#)



1 2 3 4 5 6 7 8 9 10



1 [Navigating through triangle meshes implemented as linear quadtrees](#)

100%

Michael Lee , Hanan Samet

ACM Transactions on Graphics (TOG) April 2000

Volume 19 Issue 2

Techniques are presented for navigating between adjacent triangles of greater or equal size in a hierarchical triangle mesh where the triangles are obtained by a recursive quadtree-like subdivision of the underlying space into four equilateral triangles. These techniques are useful in a number of applications, including finite element analysis, ray tracing, and the modeling of spherical data. The operations are implemented in a manner analogous to that used in a quadtree representation of d ...

2 [Solid representation and operation using extended octrees](#)

100%

Pere Brunet

ACM Transactions on Graphics (TOG) April 1990

Volume 9 Issue 2

Solid modelers must be based on reliable and fast algorithms for Boolean operations. The octree model, as well as several generalizations (polytrees, integrated polytrees, extended octrees), is specially well suited for these algorithms and can be used either as a primary or as a secondary model in solid modeling systems. This paper is concerned with a precise definition of the extended octree model that allows the representation of nonmanifold objects with planar faces and, consequently, i ...

3 [Object representation by means of nonminimal division quadtrees and octrees](#)

99%

D. Ayala , P. Brunet , R. Juan , I. Navazo


[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Search Results

Search Results for: [(polygon or mesh) and (face or patch) and level and path and vertex]
Found 544 of 119,560 searched.

Warning: Maximum result set of 200 exceeded. Consider refining.

Search within Results


[> Advanced Search](#) [> Search Help/Tips](#)

Sort by: [Title](#) [Publication](#) [Publication Date](#) [Score](#)

Results 1 - 20 of 200 [short listing](#)



1

[2](#)[3](#)[4](#)[5](#)[6](#)[7](#)[8](#)[9](#)[10](#)

1 [Kizamu: a system for sculpting digital characters](#)

94%

Ronald N. Perry , Sarah F. Frisken

Proceedings of the 28th annual conference on Computer graphics and interactive techniques
August 2001

This paper presents Kizamu, a computer-based sculpting system for creating digital characters for the entertainment industry. Kizamu incorporates a blend of new algorithms, significant technical advances, and novel user interaction paradigms into a system that is both powerful and unique.

To meet the demands of high-end digital character design, Kizamu addresses three requirements posed to us by a major production studio. First, animators and artists want *digital clay* — a ...

2 [Gross motion planning—a survey](#)

92%

Yong K. Hwang , Narendra Ahuja

ACM Computing Surveys (CSUR) September 1992
Volume 24 Issue 3

Motion planning is one of the most important areas of robotics research. The complexity of the motion-planning problem has hindered the development of practical algorithms. This paper surveys the work on gross-motion planning, including motion planners for point robots, rigid robots, and manipulators in stationary, time-varying, constrained, and movable-object environments. The general issues in motion planning are explained. Recent approaches and their performances are briefly described, a ...

3 [MAPS: multiresolution adaptive parameterization of surfaces](#)

91%


[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Search Results

Search Results for: [(identif* or path) <sentence> (polygon or mesh) <sentence> (face or patch)]
Found 43 of 119,560 searched.

Search within Results


[> Advanced Search](#) [> Search Help/Tips](#)

Sort by: [Title](#) [Publication](#) [Publication Date](#) [Score](#) [Binder](#)

Results 1 - 20 of 43 [short listing](#)



1

2

3



1 [Creating polyhedral stellations](#)

100%

Kathleen R. McKeown , Norman I. Badler

Proceedings of the 7th annual conference on Computer graphics and interactive techniques
July 1980

A process for creating and displaying stellations of a given polyhedral solid is described. A stellation is one of many star-like polyhedra which can be derived from a single solid by extending its existing faces. A program has been implemented which performs the stellation process on an input object and generates a 3-dimensional image of the stellated object on a computer graphics display screen. Pictures of icosahedron and rhombictriacontahedron stellations generated by the program are in ...

2 [Poster session: Feature preserving manifold mesh from an octree](#)

100%

Koji Ashida , Norman I. Badler

Proceedings of the eighth ACM symposium on Solid modeling and applications June 2003

We describe an algorithm to generate a manifold mesh from an octree while preserving surface features. The algorithm requires samples of a surface (coordinates) on the octree edges, along with the surface normals at those coordinates. The distinct features of the algorithm are:

- the output mesh is manifold,
- the resolution of the output mesh can be adjusted over the space with octree subdivision, and
- surface features are generally preserved.

A mesh generation algorit ...

3 [Detection of constrictions on closed polyhedral surfaces](#)

100%

F. Hétroy , D. Attali

Proceedings of the symposium on Data visualisation 2003 May 2003

We define constrictions on a surface as simple closed geodesic curves, i.e. curves whose length is locally minimal. They can be of great interests in order to cut the surface in smaller parts. In this paper, we present a method to detect constrictions on closed triangulated surfaces. Our algorithm is based on a progressive approach. First, the surface is simplified by repeated edge collapses. The simplification continues until we detect an edge whose collapse would change the topology of the surface ...

4 Applications of random sampling in computational geometry, II

100%

4 K. L. Clarkson

Proceedings of the fourth annual symposium on Computational geometry January 1988

Random sampling is used for several new geometric algorithms. The algorithms are “Las Vegas,” and their expected bounds are with respect to the random behavior of the algorithms. One algorithm reports all the intersecting pairs of a set of line segments in the plane, and requires $O((A + n \log n))$ expected time, where A is the size of the answer, the number of intersecting pairs reported. The a ...

5 A multisided generalization of Bézier surfaces

100%

4 Charles T. Loop , Tony D. DeRose

ACM Transactions on Graphics (TOG) July 1989

Volume 8 Issue 3

In this paper we introduce a class of surface patch representations, called S-patches, that unify and generalize triangular and tensor product Bézier surfaces by allowing patches to be defined over any convex polygonal domain; hence, S-patches may have any number of boundary curves. Other properties of S-patches are geometrically meaningful control points, separate control over positions and derivatives along boundary curves, and a geometric construction algorithm based on de Casteljau ...

6 Session 5: simplification and meshes: User-controlled creation of multiresolution meshes

100%

4 Erik Pojar , Dieter Schmalstieg

Proceedings of the 2003 symposium on Interactive 3D graphics April 2003

We present a tool for the user-controlled creation of multiresolution meshes. Most automatic mesh reduction methods are not able to identify mesh regions of high semantic or functional importance, for example the face of a character model or areas deformed by animation. To address this problem, we present a method allowing a user to provide importance weights for mesh regions to control the automatic simplification process. To demonstrate the usefulness of this approach in a real world setting, ...

7 Mesher: Adjacency and incidence framework: a data structure for efficient and fast management of multiresolution meshes

100%

4 Frutuoso G. M. Silva , Abel J. P. Gomes

Proceedings of the 1st international conference on Computer graphics and interactive techniques in Australasia and South East Asia February 2003

This paper introduces a concise and responsiveness data structure, called AIF (Adjacency and Incidence Framework), for multiresolution meshes, as well as a new simplification algorithm based on the planarity of neighboring faces. It is an optimal data structure for polygonal meshes, manifold and non-manifold, which means that a minimal number of direct and indirect accesses are required to retrieve adjacency and incidence information from it. These querying tools are necessary for dynamic multir ...

- 8 Session P15: multidimensional, motion, and information visualization: A radial focus+context visualization for multi-dimensional functions 100%
Sanjini Jayaraman , Chris North
Proceedings of the conference on Visualization '02 October 2002
The analysis of multidimensional functions is important in many engineering disciplines, and poses a major problem as the number of dimensions increases. Previous visualization approaches focus on representing three or fewer dimensions at a time. This paper presents a new focus+context visualization that provides an integrated overview of an entire multidimensional function space, with uniform treatment of all dimensions. The overview is displayed with respect to a user-controlled polar focal po ...
- 9 Session P4: compression and simplification: TetFusion: an algorithm for rapid tetrahedral mesh simplification 100%
Prashant Chopra , Joerg Meyer
Proceedings of the conference on Visualization '02 October 2002
This paper introduces an algorithm for rapid progressive simplification of tetrahedral meshes: *TetFusion*. We describe how a simple geometry decimation operation steers a rapid and controlled progressive simplification of tetrahedral meshes, while also taking care of complex mesh-inconsistency problems. The algorithm features a high decimation ratio per step, and inherently discourages any cases of self-intersection of boundary, element-boundary intersection at concave boundary-regions, an ...
- 10 Robust epsilon visibility 100%
Florent Duguet , George Drettakis
ACM Transactions on Graphics (TOG) , Proceedings of the 29th annual conference on Computer graphics and interactive techniques July 2002
Volume 21 Issue 3
Analytic visibility algorithms, for example methods which compute a subdivided mesh to represent shadows, are notoriously unrobust and hard to use in practice. We present a new method based on a generalized definition of extremal stabbing lines, which are the extremities of shadow boundaries. We treat scenes containing multiple edges or vertices in degenerate configurations, (e.g., collinear or coplanar). We introduce a robust ϵ method to determine whether each generalized extremal stabb ...
- 11 A procedural approach to authoring solid models 100%
Barbara Cutler , Julie Dorsey , Leonard McMillan , Matthias Müller , Robert Jagnow
ACM Transactions on Graphics (TOG) , Proceedings of the 29th annual conference on Computer graphics and interactive techniques July 2002
Volume 21 Issue 3
We present a procedural approach to authoring layered, solid models. Using a simple scripting language, we define the internal structure of a volume from one or more input meshes. Sculpting and simulation operators are applied within the context of the language to shape and modify the model. Our framework treats simulation as a modeling operator rather than simply as a tool for animation, thereby suggesting a new paradigm for modeling as well as a new level of abstraction for interacting with si ...
- 12 Static and kinetic geometric spanners with applications 100%

- 4 Menelaos I. Karavelas , Leonidas J. Guibas
Proceedings of the twelfth annual ACM-SIAM symposium on Discrete algorithms January 2001

It is well known that the Delaunay Triangulation is a spanner graph of its vertices. In this paper we show that any bounded aspect ratio triangulation in two and three dimensions is a spanner graph of its vertices as well. We extend the notion of spanner graphs to environments with obstacles and show that both the Constrained Delaunay Triangulation and bounded aspect ratio conforming triangulations are spanners with respect to the corresponding visibility graph. We also show how to kinetiz ...

- 13 Frame-to-frame coherence and the hidden surface computation: constraints for a convex world 100%

4 H. Hubschman , S. W. Zucker
ACM Transactions on Graphics (TOG) April 1982
Volume 1 Issue 2

- 14 A Characterization of Ten Hidden-Surface Algorithms 100%

4 Evan E. Sutherland , Robert F. Sproull , Robert A. Schumacker
ACM Computing Surveys (CSUR) January 1974
Volume 6 Issue 1

- 15 Shadows for cel animation 100%

4 Lena Petrovi? , Brian Fujito , Lance Williams , Adam Finkelstein
Proceedings of the 27th annual conference on Computer graphics and interactive techniques July 2000

We present a semi-automatic method for creating shadow mattes in cel animation. In conventional cel animation, shadows are drawn by hand, in order to provide visual cues about the spatial relationships and forms of characters in the scene. Our system creates shadow mattes based on hand-drawn characters, given high-level guidance from the user about depths of various objects. The method employs a scheme for “inflating” a 3D figure based on hand-drawn art. It provides simple tools ...

- 16 Lapped textures 100%

4 Emil Praun , Adam Finkelstein , Hugues Hoppe
Proceedings of the 27th annual conference on Computer graphics and interactive techniques July 2000

We present for creating texture over an surface mesh using an example 2D texture. The approach is to identify interesting regions (texture patches) in the 2D example, and to repeatedly paste them onto the surface until it is completely covered. We call such a collection of overlapping patches a lapped texture. It is rendered using compositing operations, either into a traditional global texture map during a preprocess, or directly with the surface at runtime ...

- 17 Face fixer: compressing polygon meshes with properties 100%


4 Martin Isenburg , Jack Snoeyink
Proceedings of the 27th annual conference on Computer graphics and interactive techniques July 2000

Most schemes to compress the topology of a surface mesh have been developed for the lowest common denominator: triangulated meshes. We propose a scheme that handles the topology of

arbitrary polygon meshes. It encodes meshes directly in their polygonal representation and extends to capture face groupings in a natural way. Avoiding the triangulation step we reduce the storage costs for typical polygon models that have group structures and property data.

18 Parallel multigrid solver for 3D unstructured finite element problems


100%

 Mark Adams , James W. Demmel

Proceedings of the 1999 ACM/IEEE conference on Supercomputing (CDROM) January 1999

19 Implant sprays: compression of progressive tetrahedral mesh connectivity


100%

 Renato Pajarola , Jarek Rossignac , Andrzej Szymczak

Proceedings of the conference on Visualization '99: celebrating ten years October 1999
Irregular tetrahedral meshes, which are popular in many engineering and scientific applications, often contain a large number of vertices. A mesh of V vertices and T tetrahedra requires $48 \cdot V$ bits or less to store the vertex coordinates, $4 \cdot V \log 2$ bits to store the tetrahedra-vertex incidence relations, also called connectivity information, and $k \cdot V$ bits to store the k -bit value samples associated with the vertices. Given that T is 5 to 7 times ...



20 Optimization problems related to zigzag pocket machining

100%

 Esther M. Arkin , Martin Held , Christopher L. Smith

Proceedings of the seventh annual ACM-SIAM symposium on Discrete algorithms January 1996

Results 1 - 20 of 43 [short listing](#)

 [Prev Page](#) 1 2 [3](#) [Next Page](#) 

The ACM Portal is published by the Association for Computing Machinery. Copyright © 2003 ACM, Inc.



[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Search Results

Search Results for: [unique* <near> identif* <sentence> (polygon or mesh) <sentence> (face or patch)

] Found 2 of 119,560 searched.

Search within Results

[Go](#) [> Advanced Search](#) [> Search Help/Tips](#)

Sort by: [Title](#) [Publication](#) [Publication Date](#) [Score](#) [Binder](#)

Results 1 - 2 of 2 [short listing](#)

1 [Creating polyhedral stellations](#)

100%

Kathleen R. McKeown , Norman I. Badler

Proceedings of the 7th annual conference on Computer graphics and interactive techniques
July 1980

A process for creating and displaying stellations of a given polyhedral solid is described. A stellation is one of many star-like polyhedra which can be derived from a single solid by extending its existing faces. A program has been implemented which performs the stellation process on an input object and generates a 3-dimensional image of the stellated object on a computer graphics display screen. Pictures of icosahedron and rhombictriacontahedron stellations generated by the program are in ...

2 [Building a scaleable geo-spatial DBMS: technology, implementation, and evaluation](#)

100%

Jignesh Patel , JieBing Yu , Navin Kabra , Kristin Tufte , Biswadeep Nag , Josef Burger , Nancy Hall , Karthikeyan Ramasamy , Roger Lueder , Curt Ellmann , Jim Kupsch , Shelly Guo , Johan Larson , David De Witt , Jeffrey Naughton

ACM SIGMOD Record , Proceedings of the 1997 ACM SIGMOD international conference on Management of data June 1997
Volume 26 Issue 2

This paper presents a number of new techniques for parallelizing geo-spatial database systems and discusses their implementation in the Paradise object-relational database system. The effectiveness of these techniques is demonstrated using a variety of complex geo-spatial queries over a 120 GB global geo-spatial data set.

Results 1 - 2 of 2 [short listing](#)

The ACM Portal is published by the Association for Computing Machinery. Copyright © 2003 ACM, Inc.

[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent & Trademark Office



Try the *new* Portal design
Give us your opinion after using it.

Search Results

Search Results for: [(lounsbery)]
Found 115 of 119,560 searched.

Search within Results

[> Advanced Search](#) [> Search Help/Tips](#)

Sort by: [Title](#) [Publication](#) [Publication Date](#) [Score](#) [Binder](#)

Results 1 - 20 of 115 [short listing](#)

[1](#) [2](#) [3](#) [4](#) [5](#) [6](#)

- 1 [Multiresolution analysis for surfaces of arbitrary topological type](#) 99%
 Michael Lounsbery , Tony D. DeRose , Joe Warren
ACM Transactions on Graphics (TOG) January 1997
Volume 16 Issue 1
Multiresolution analysis and wavelets provide useful and efficient tools for representing functions at multiple levels of detail. Wavelet representations have been used in a broad range of applications, including image compression, physical simulation, and numerical analysis. In this article, we present a new class of wavelets, based on subdivision surfaces, that radically extends the class of representable functions. Whereas previous two-dimensional methods were restricted to functions dif ...
- 2 [Multiresolution analysis of arbitrary meshes](#) 97%
 Matthias Eck , Tony DeRose , Tom Duchamp , Hugues Hoppe , Michael Lounsbery , Werner Stuetzle
Proceedings of the 22nd annual conference on Computer graphics and interactive techniques September 1995
- 3 [Interactive multiresolution surface viewing](#) 87%
 Andrew Certain , Jovan Popovic , Tony DeRose , Tom Duchamp , David Salesin , Werner Stuetzle
Proceedings of the 23rd annual conference on Computer graphics and interactive techniques August 1996
- 4 [Interactive multiresolution mesh editing](#) 85%
 Denis Zorin , Peter Schröder , Wim Sweldens
Proceedings of the 24th annual conference on Computer graphics and interactive techniques August 1997

- 5 Meshes: Consistent parametrization by quinary subdivision for remeshing and mesh metamorphosis 84%
Jian Liang Lin , Jung Hong Chuang , Cheng Chung Lin , Chih Chun Chen
Proceedings of the 1st international conference on Computer graphics and interactive techniques in Australasia and South East Asia February 2003
The vertex correspondence establishment among multiple objects is a versatile operation in computer graphics and geometry processing. We propose a systematic method called *recursive quinary subdivision* to efficiently find a dissection for a meshed object of genus-zero with little user input. The process can be easily extended to multiple objects, taking into account the alignment of extra feature points for applications such as mesh metamorphosis, to derive a common dissection. Based on t ...
- 6 Session D: Geometry: View-dependent refinement of multiresolution meshes with subdivision connectivity 84%
Daniel I. Azuma , Daniel N. Wood , Brian Curless , Tom Duchamp , David H. Salesin , Werner Stuetzle
Proceedings of the 2nd international conference on Computer graphics, virtual Reality, visualisation and interaction in Africa February 2003
We present a view-dependent level-of-detail algorithm for triangle meshes with subdivision connectivity. The algorithm is more suitable for textured meshes of arbitrary topology than existing progressive mesh-based schemes. It begins with a wavelet decomposition of the mesh, and, per frame, finds a partial sum of wavelets necessary for high-quality renderings from that frame's viewpoint. We present a screen-space error metric that measures both geometric and texture deviation and tends to outper ...
- 7 Model Simplification: Biorthogonal wavelets for subdivision volumes 84%
Martin Bertram
Proceedings of the seventh ACM symposium on Solid modeling and applications June 2002
We present a biorthogonal wavelet construction based on Catmull-Clark-style subdivision volumes. Our wavelet transform is the three-dimensional extension of a previously developed construction of subdivision-surface wavelets that was used for multiresolution modeling of large-scale isosurfaces. Subdivision surfaces provide a flexible modeling tool for surfaces of arbitrary topology and for functions defined thereon. Wavelet representations add the ability to compactly represent large-scale geome ...
- 8 Bicubic subdivision-surface wavelets for large-scale isosurface representation and visualization 84%
Martin Bertram , Mark A. Duchaineau , Bernd Hamann , Kenneth I. Joy
Proceedings of the conference on Visualization '00 October 2000
- 9 MetaStream 84%
Vadim Abadjev , Miguel del Rosario , Alexei Lebedev , Alexander Migdal , Victor Paskhaver
Proceedings of the fourth symposium on Virtual reality modeling language February 1999
- 10 Progressive meshes 84%
Hugues Hoppe
Proceedings of the 23rd annual conference on Computer graphics and interactive

techniques August 1996

- 11 Multiresolution curves 84%
Adam Finkelstein , David H. Salesin
Proceedings of the 21st annual conference on Computer graphics and interactive techniques
July 1994
We describe a multiresolution curve representation, based on wavelets, that conveniently supports a variety of operations: smoothing a curve; editing the overall form of a curve while preserving its details; and approximating a curve within any given error tolerance for scan conversion. We present methods to support continuous levels of smoothing as well as direct manipulation of an arbitrary portion of the curve; the control points, as well as the discrete nature of the underlying hierarchy ...
- 12 MAPS: multiresolution adaptive parameterization of surfaces 83%
Aaron W. F. Lee , Wim Sweldens , Peter Schröder , Lawrence Cowsar , David Dobkin
Proceedings of the 25th annual conference on Computer graphics and interactive techniques
July 1998
- 13 Cut-and-paste editing of multiresolution surfaces 82%
Henning Biermann , Ioana Martin , Fausto Bernardini , Denis Zorin
ACM Transactions on Graphics (TOG) , Proceedings of the 29th annual conference on Computer graphics and interactive techniques July 2002
Volume 21 Issue 3
Cutting and pasting to combine different elements into a common structure are widely used operations that have been successfully adapted to many media types. Surface design could also benefit from the availability of a general, robust, and efficient cut-and-paste tool, especially during the initial stages of design when a large space of alternatives needs to be explored. Techniques to support cut-and-paste operations for surfaces have been proposed in the past, but have been of limited usefulness ...
- 14 Displaced subdivision surfaces 82%
Aaron Lee , Henry Moreton , Hugues Hoppe
Proceedings of the 27th annual conference on Computer graphics and interactive techniques
July 2000
In this paper we introduce a new surface representing, the displaced subdivision surface. It represents a detailed surface model as a scalar-valued displacement over a smooth domain surface. Our representation defines both the domain surface and the displacement function using a unified subdivision framework, allowing for simple and efficient evaluation of analytic surface properties. We present a simple, automatic scheme for converting detailed geometric models into such a ...
- 15 Prefix compression of sparse binary strings 82%
David Salomon
Crossroads March 2000
Volume 6 Issue 3
- 16 XVL: a compact and qualified 3D representation with lattice mesh and surface for the Internet 82%

- 4 Akira Wakita , Makoto Yajima , Tsuyoshi Harada , Hiroshi Toriya , Hiroaki Chiyokura
Proceedings of the fifth symposium on Virtual reality modeling language (Web3D-VRML)
February 2000

Computer graphics systems and CAD/CAM systems are widely used and an abundance of 3D-Data in various fields exists. However, based on the VRML technique, it is difficult to send such 3D-Data through the Internet, because of the large data size. Transmission of practical and highly detailed 3D-Data through the Internet becomes a primary requirement. Therefore, a compact and qualified 3D-Data representation method is greatly required. This paper describes XVL (eXtended VRML with Lat ...

- 17 Compression of time-dependent geometry 82%

- 4 Jerome Edward Lengyel
Proceedings of the 1999 symposium on Interactive 3D graphics April 1999

- 18 Efficient, fair interpolation using Catmull-Clark surfaces 82%

- 4 Mark Halstead , Michael Kass , Tony DeRose
Proceedings of the 20th annual conference on Computer graphics and interactive techniques
September 1993

- 19 Surfaces from contours 82%

- 4 David Meyers , Shelley Skinner , Kenneth Sloan
ACM Transactions on Graphics (TOG) July 1992
Volume 11 Issue 3
This paper is concerned with the problem of reconstructing the surfaces of three-dimensional objects, given a collection of planar contours representing cross-sections through the objects. This problem has important applications in biomedical research and instruction, solid modeling, and industrial inspection. The method we describe produces a triangulated mesh from the data points of the contours which is then used in conjunction with a piecewise parametric surface-fitting algorithm ...

- 20 Meshes: Adjacency and incidence framework: a data structure for efficient and fast management of multiresolution meshes 82%

- 4 Frutuoso G. M. Silva , Abel J. P. Gomes
Proceedings of the 1st international conference on Computer graphics and interactive techniques in Australasia and South East Asia February 2003
This paper introduces a concise and responsiveness data structure, called AIF (Adjacency and Incidence Framework), for multiresolution meshes, as well as a new simplification algorithm based on the planarity of neighboring faces. It is an optimal data structure for polygonal meshes, manifold and non-manifold, which means that a minimal number of direct and indirect accesses are required to retrieve adjacency and incidence information from it. These querying tools are necessary for dynamic multir ...

EIC
2700

in C

Computer Graphics:
Principles and Practice

♦
Foley
van Dam
Feiner
Hughes

T
385
.C5735
1996
c.28



THE
SYSTEMS
PROGRAMMING
SERIES

Computer Graphics: Principles and Practice

SECOND EDITION in C

Foley ♦ van Dam ♦ Feiner ♦ Hughes

67/515,517

Searched

SECOND EDITION IN C

Computer Graphics

PRINCIPLES AND PRACTICE

01-27-00 P10:07 IN

James D. Foley

Georgia Institute of Technology

Andries van Dam

Brown University

Steven K. Feiner

Columbia University

John F. Hughes

Brown University



ADDISON-WESLEY PUBLISHING COMPANY

Reading, Massachusetts • Menlo Park, California • New York
Don Mills, Ontario • Wokingham, England • Amsterdam • Bonn
Sydney • Singapore • Tokyo • Madrid • San Juan • Milan • Paris

Sponsoring Editor: Peter S. Gordon
Production Supervisor: Bette J. Aaronson
Production Supervisor for the C edition: Juliet Silveri
Copy Editor: Lyn Dupré
Text Designer: Herb Caswell
Technical Art Consultant: Joseph K. Vetere
Illustrators: C&C Associates
Cover Designer: Marshall Henrichs
Manufacturing Manager: Roy Logan

This book is in the **Addison-Wesley Systems Programming Series**
Consulting editors: IBM Editorial Board

Library of Congress Cataloging-in-Publication Data

Computer graphics: principles and practice / James D. Foley . . . [et
al.]. — 2nd ed. in C.
p. cm.
Includes bibliographical references and index.
ISBN 0-201-84840-6
1. Computer graphics. I. Foley, James D., 1942–
T385.C5735 1996
006.6'6—dc20

95-13631
CIP

Reprinted with corrections, July 1997.

Cover: "Dutch Interior," after Vermeer, by J. Wallace, M. Cohen, and D. Greenberg, Cornell University
(Copyright © 1987 Cornell University, Program of Computer Graphics.)

Many of the designations used by manufacturers and sellers to distinguish their products are claimed as trademarks. Where those designations appear in this book, and Addison-Wesley was aware of a trademark claim, the designations have been printed in initial caps or all caps.

The programs and applications presented in this book have been included for their instructional value. They are not guaranteed for any particular purpose. The publisher and the author do not offer any warranties or representations, nor do they accept any liabilities with respect to the programs or applications.

Reprinted with corrections November 1992, November 1993, and July 1995.

Copyright © 1996, 1990 by Addison-Wesley Publishing Company, Inc.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher. Printed in the United States of America.

Text printed on recycled and acid-free paper.

ISBN 0201848406

12 1314151617 DOC 02 01 00 99

12th Printing November 1999

To Mary

To Debb
my child

To Jenni,

To my fa
my father

And to al

xx Contents

10.4	Input Handling in Window Systems	447
10.5	Interaction-Technique Toolkits	451
10.6	User-Interface Management Systems	456
	Exercises	468

CHAPTER 11

REPRESENTING CURVES AND SURFACES		471
11.1	Polygon Meshes	473
11.2	Parametric Cubic Curves	478
11.3	Parametric Bicubic Surfaces	516
11.4	Quadric Surfaces	528
11.5	Summary	529
	Exercises	530

CHAPTER 12

SOLID MODELING		533
12.1	Representing Solids	534
12.2	Regularized Boolean Set Operations	535
12.3	Primitive Instancing	539
12.4	Sweep Representations	540
12.5	Boundary Representations	542
12.6	Spatial-Partitioning Representations	548
12.7	Constructive Solid Geometry	557
12.8	Comparison of Representations	558
12.9	User Interfaces for Solid Modeling	561
12.10	Summary	561
	Exercises	562

CHAPTER 13

ACHROMATIC AND COLORED LIGHT		563
13.1	Achromatic Light	563
13.2	Chromatic Color	574
13.3	Color Models for Raster Graphics	584
13.4	Reproducing Color	599
13.5	Using Color in Computer Graphics	601
13.6	Summary	603
	Exercises	603

CHAPTER 14

THE QUEST FOR VISUAL REALISM		605
14.1	Why Realism?	606
14.2	Fundamental Difficulties	607
14.3	Rendering Techniques for Line Drawings	609

14.4	Rendering Tech
14.5	Improved Objec
14.6	Dynamics
14.7	Stereopsis
14.8	Improved Displ
14.9	Interacting with
14.10	Aliasing and Ar
14.11	Summary
	Exercises

CHAPTER 15

VISIBLE-SURFACE	
15.1	Functions of Tw
15.2	Techniques for E
15.3	Algorithms for V
15.4	The z-Buffer Alg
15.5	List-Priority Alg
15.6	Scan-Line Algori
15.7	Area-Subdivision
15.8	Algorithms for C
15.9	Algorithms for C
15.10	Visible-Surface R
15.11	Summary
	Exercises

CHAPTER 16

ILLUMINATION AN	
16.1	Illumination Mod
16.2	Shading Models 1
16.3	Surface Detail
16.4	Shadows
16.5	Transparency
16.6	Interobject Reflec
16.7	Physically Based
16.8	Extended Light S
16.9	Spectral Sampling
16.10	Improving the Cal
16.11	Global Illuminatio
16.12	Recursive Ray Tra
16.13	Radiosity Method
16.14	The Rendering Pi
16.15	Summary
	Exercises

occupancy enumeration is often used in biomedical applications to represent volumetric data obtained from sources such as computerized axial tomography (CAT) scans.

For all of its advantages, however, spatial-occupancy enumeration has a number of obvious failings that parallel those of representing a 2D shape by a 1-bit-deep bitmap. There is no concept of "partial" occupancy. Thus, many solids can be only approximated; the torus of Fig. 12.20 is an example. If the cells are cubes, then the only objects that can be represented exactly are those whose faces are parallel to the cube sides and whose vertices fall exactly on the grid. Like pixels in a bitmap, cells may in principle be made as small as desired to increase the accuracy of the representation. Space becomes an important issue, however, since up to n^3 occupied cells are needed to represent an object at a resolution of n voxels in each of three dimensions.

12.6.3 Octrees

Octrees are a hierarchical variant of spatial-occupancy enumeration, designed to address that approach's demanding storage requirements. Octrees are in turn derived from *quadtrees*, a 2D representation format used to encode images (see Section 17.7). As detailed in Samet's comprehensive survey [SAME84], both representations appear to have been discovered independently by a number of researchers, quadtrees in the late 1960s to early 1970s [e.g., WARN69; KLIN71] and octrees in the late 1970s to early 1980s [e.g., HUNT78; REDD78; JACK80; MEAG80; MEAG82a].

The fundamental idea behind both the quadtree and octree is the divide-and-conquer power of binary subdivision. A quadtree is derived by successively subdividing a 2D plane in both dimensions to form quadrants, as shown in Fig. 12.21. When a quadtree is used to represent an area in the plane, each quadrant may be full, partially full, or empty (also called black, gray, and white, respectively), depending on how much of the quadrant intersects the area. A partially full quadrant is recursively subdivided into subquadrants. Subdivision continues until all quadrants are homogeneous (either full or empty) or until a predetermined cutoff depth is reached. Whenever four sibling quadrants are uniformly full or empty, they are deleted and their partially full parent is replaced with a full or empty node. (A bottom-up approach can be used instead to avoid this deletion and merging process [SAME90b].) In Fig. 12.21, any partially full node at the cutoff depth is classified as full. The successive subdivisions can be represented as a tree with partially full quadrants at the internal nodes and full and empty quadrants at the leaves, as shown in Fig. 12.22.




Fig. 12.21 An object represented using (a) spatial-occupancy enumeration (b) quadtree.




Fig. 12.22 Quad full, E = empty.

This idea can be co
15.7.1. If the crite
that are above or
representation becc
quadtree, except th
in Fig. 12.23.

Quadrants are
to 7. Since no stan
used. Quadrants an
their parent: NW, N
left (L) and right (R
LDB, RUF, RUB, .




Fig. 12.22 Quadtree data structure for the object in Fig. 12.21. F = full, P = partially full, E = empty.

This idea can be compared to the Warnock area-subdivision algorithm discussed in Section 15.7.1. If the criteria for classifying a node as homogeneous are relaxed, allowing nodes that are above or below some threshold to be classified as full or empty, then the representation becomes more compact, but less accurate. The octree is similar to the quadtree, except that its three dimensions are recursively subdivided into octants, as shown in Fig. 12.23.

Quadrants are often referred to by the numbers 0 to 3, and octants by numbers from 0 to 7. Since no standard numbering scheme has been devised, mnemonic names are also used. Quadrants are named according to their compass direction relative to the center of their parent: NW, NE, SW, and SE. Octants are named similarly, distinguishing between left (L) and right (R), up (U) and down (D), and front (F) and back (B): LUF, LUB, LDF, LDB, RUF, RUB, RDF, and RDB.




Fig. 12.23 Octree enumeration. Octant 0 is not visible.

With the exception of a few worst cases, it can be shown that the number of nodes in a quadtree or octree representation of an object is proportional to the object's perimeter or surface, respectively [HUNT78; MEAG80]. This relation holds because node subdivision arises only from the need to represent the boundary of the object being encoded. The only internal nodes that are split are those through which part of the boundary passes. Thus, any operation on one of these data structures that is linear in the number of nodes it contains also executes in time proportional to the size of its perimeter or area.

Although the divide-and-conquer approach of the quadtree and octree can be generalized to objects of arbitrary dimension, it is also possible to represent objects using only binary trees. Rather than dividing along all axes at each node of the tree, a *bintree* partitions space into equal halves about a single axis at each node, cycling through a new axis at each level [TAMM84]. A bintree often has more nodes than its equivalent quadtree or octree, but has at most the same number of leaves; as well, many processing algorithms can be formulated more simply for bintrees.

Boolean set operations and transformations. Much work has been done on developing efficient algorithms for storing and processing quadtrees and octrees [SAME84; SAME90a; SAME90b]. For example, Boolean set operations are straightforward for both quadtrees and octrees [HUNT79]. To compute the union or intersection U of two trees, S and T , we traverse both trees top-down in parallel. Figure 12.24 shows the operations for quadtrees; the generalization to octrees is straightforward. Each matching pair of nodes is examined. Consider the case of union. If either of the nodes in the pair is black, then a corresponding black node is added to U . If one of the pair's nodes is white, then the corresponding node is created in U with the value of the other node in the pair. If both nodes of the pair are gray, then a gray node is added to U , and the algorithm is applied recursively to the pair's children. In this last case, the children of the new node in U must be inspected after the algorithm has been applied to them. If they are all black, they are deleted and their parent in U is changed from gray to black. The algorithm for performing intersection is similar, except the roles of black and white are interchanged. If either of the nodes in a pair is white, then a corresponding white node is added to U . If one of the pair's nodes is black, then the corresponding node is created in U with the value of the other node in the pair. If both nodes of the pair are gray, then a gray node is added to U , and the algorithm is applied recursively to the pair's children. As in the union algorithm, if both nodes are gray, then after the algorithm has been applied to the children of the new node in U , the children must be inspected. In this case, if they are all white, they are deleted and their parent in U must be changed from gray to white.

It is easy to perform simple transformations on quadtrees and octrees. For example, rotation about an axis by multiples of 90° is accomplished by recursively rotating the children at each level. Scaling by powers of 2 and reflections are also straightforward. Translations are somewhat more complex, as are general transformations. In addition, as in spatial-occupancy enumeration in general, the problem of aliasing under general transformations is severe.

Neighbor finding. One important operation in quadtrees and octrees is finding a node's *neighbor*; that is, finding a node that is adjacent to the original node (sharing a face, edge, or vertex) and of equal or greater size. A quadtree node has neighbors in eight possible



Fig. 12.24 Performance of quadtree. (b) Object

directions. Its N, S, NE, SW, and SE neighbors in 26 positions and 8 neighbors at Samet [SAME]. The method starts common ancestor downward to find finding the common simplest case is find U, D, F, or B. As will be the first no the search is for at reached from an L reached from one




Fig. 12.24 Performing Boolean set operations on quadrees. (a) Object S and its quadtree. (b) Object T and its quadtree. (c) $S \cup T$. (d) $S \cap T$.

directions. Its N, S, E, W neighbors are neighbors along a common edge, whereas its NW, NE, SW, and SE neighbors are neighbors along a common vertex. An octree node has neighbors in 26 possible directions: 6 neighbors along a face, 12 neighbors along an edge, and 8 neighbors along a vertex.

Samet [SAME89a] describes a way to find a node's neighbor in a specified direction. The method starts at the original node and ascends the quadtree or octree until the first common ancestor of the original node and neighbor is found. The tree is then traversed downward to find the desired neighbor. Two problems must be solved efficiently here: finding the common ancestor and determining which of its descendants is the neighbor. The simplest case is finding an octree node's neighbor in the direction d of one of its faces: L, R, U, D, F, or B. As we ascend the tree starting at the original node, the common ancestor will be the first node that is not reached from a child on the node's d side. For example, if the search is for an L neighbor, then the first common ancestor is the first node that is not reached from an LUF, LUB, LDF, or LDB child. This is true because a node that has been reached from one of these children cannot have any child that is left of (is an L neighbor of)

the original node. When the common ancestor is found, its subtree is descended in a mirror image of the path from the original node to the ancestor, reflected about the common border. Only part of the reflected path is followed if the neighbor is larger than the original node.

A similar method can be used to find a quadtree node's neighbor in the direction of one of its edges. For example, to find the N neighbor of node A of Fig. 12.25, we begin at A, which is a NW child, and follow the path depicted by the thick line in the figure. We ascend from the NW to its parent, from the NW again to its grandparent, and finally from the SW to its great grandparent, the root, stopping because we have approached it from an S node, rather than from an N node. We then follow the mirror-image path downward (reflected about the N-S border), to the root's NW child, and finally to this node's SW child, which is a leaf. Samet [SAME89a] describes the more elaborate algorithms for finding edge and vertex neighbors in octrees, and provides an elegant recursive implementation that uses table lookup to perform such operations as computing the reflected path.

Linear notations. Although a tree data structure with pointers might at first seem necessary to represent a quadtree or octree, pointerless notations are possible. In the *linear quadtree* or *linear octree* notation [GARG82], each full node is represented as a sequence of digits that represents its fully qualified address. There are as many digits as there are levels. Only black leaf nodes need to be stored to represent the object. Nodes that are not at the lowest level include an additional padding character (e.g., “X”) in each of their trailing

digits. For example, 20X, 21X, 220, 221 (conveniently representing padding) represents a posterior distribution of the object in

A number of linear-octree representations present an algorithm in successive passes, considered first. Each node is internal to the object (Each neighbor's code.) Any other nodes these nodes is brother algorithm is repeated are considered. The

PM octrees. A combine octrees at which the object is octrees (*PM* stands The octree is recur In addition to full kinds of partially f faces and edges; ed nodes, which are c simple geometries, algorithms that ma NAVA89].

Section 18.11.
Section 15.8 discus:

12.6.4 Binary

Otrees recursively
bisect all three din
(BSP) trees recursi
arbitrary orientatic
used in determinin
and Naylor [THIB
Each internal node
for each side of th
behind or inside th
half-space on a sid
if the half-space i




Fig. 12.25 Finding the neighbor of a quadtree node.

digits. For example, a linear octree can be encoded compactly using base-9 numbers (conveniently represented with 4 bits per digit), with 0 through 7 specifying octants and 8 indicating padding. The nodes in the linear octree are stored in sorted order, which represents a postorder traversal of the octree. For example, the linear quadtree representation of the object in Fig. 12.21 is 00X, 010, 011, 020, 022, 100, 102, 103, 12X, 130, 132, 20X, 21X, 220, 222, 223, 230, 231, 232, 3XX.

A number of operations can be performed efficiently with the linear-quadtree or linear-octree representation. For example, Atkinson, Gargantini, and Ramanath [ATK184] present an algorithm for determining the voxels that form an octree's border by making successive passes over a list of the octree's nodes. Full nodes of the largest size are considered first. Each such node that abuts full nodes of the same size on all six sides is internal to the object and is therefore not part of the border; it is eliminated from the list. (Each neighbor's code may be derived by simple arithmetic manipulation of the node's code.) Any other node of this size may contain voxels that are part of the border; each of these nodes is broken into its eight constituent nodes, which replace it in the list. The algorithm is repeated for successively smaller node sizes, stopping after voxel-sized nodes are considered. Those nodes remaining are all the voxels on the object's border.

PM octrees. A number of researchers have developed hybrid representations that combine octrees and b-reps to maintain the precise geometry of the original b-rep from which the object is derived [HUNT81; QUIN82; AYAL85; CARL85; FUJI85]. These *PM octrees* (*PM* stands for Polygonal Map) expand on a similar quadtree variant [SAME90a]. The octree is recursively divided into nodes until the node is one of five different leaf types. In addition to full and empty, three new leaf nodes are introduced that are actually special kinds of partially full nodes: vertex nodes, which contain a single vertex and its connected faces and edges; edge nodes, which contain part of a single edge and its faces; and surface nodes, which are cut by a piece of a single face. Restricting the new leaf types to a set of simple geometries, each of which divides the node into exactly two parts, simplifies the algorithms that manipulate the representation, such as Boolean set operations [CARL87; NAVA89].

Section 18.11.4 discusses a number of architectures based on voxel and octree models. Section 15.8 discusses visible-surface algorithms for octrees.

12.6.4 Binary Space-Partitioning Trees

Octrees recursively divide space by planes that are always mutually perpendicular and that bisect all three dimensions at each level of the tree. In contrast, *binary space-partitioning* (BSP) trees recursively divide space into pairs of subspaces, each separated by a plane of arbitrary orientation and position. The binary-tree data structure created was originally used in determining visible surfaces in graphics, as described in Section 15.5.2. Thibault and Naylor [THIB87] later introduced the use of BSP trees to represent arbitrary polyhedra. Each internal node of the BSP tree is associated with a plane and has two child pointers, one for each side of the plane. Assuming that normals point out of an object, the left child is behind or inside the plane, whereas the right child is in front of or outside the plane. If the half-space on a side of the plane is subdivided further, then its child is the root of a subtree; if the half-space is homogeneous, then its child is a leaf, representing a region either

[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

michael lounsbery

Google Search

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)Searched the web for **michael lounsbery**.

Results 1 - 10 of about 2,120. Search took 0.47 seconds.

Michael - Buy Books and More on eBay

Sponsored Link

www.eBay.com eBay - The World's Online Marketplace

[PDF] Copyright 1994 John Michael LounsberyFile Format: PDF/Adobe Acrobat - [View as HTML](#)Page 1. c Copyright 1994 John **Michael Lounsbery** Page 2. Multiresolution

Analysis for Surfaces of Arbitrary Topological Type by John ...

grail.cs.washington.edu/theses/LounsberyPhd.pdf - [Similar pages](#)[\[ps\]grail.cs.washington.edu/theses/LounsberyPhd.ps.gz](#)File Format: Adobe PostScript - [View as Text](#)... c fl Copyright 1994. John **Michael Lounsbery** Pass1: Page -1 Multiresolution Analysis for Surfaces of Arbitrary Topological Type. by John **Michael Lounsbery**. ...[Similar pages](#)[[More results from grail.cs.washington.edu](#)]**DBLP: Michael Lounsbery**dblp.uni-trier.de **Michael Lounsbery**. ... 2, EE, **Michael Lounsbery**, Tony DeRose, Joe D.

Warren: Multiresolution Analysis for Surfaces of Arbitrary Topological Type. ...

www.informatik.uni-trier.de/~ley/db/indices/ a-tree//Lounsbery:Michael.html - 3k - [Cached](#) - [Similar pages](#)**DBLP: Tony DeRose**... SIGGRAPH 1998: 85-94. 1997. 13, EE, **Michael Lounsbery**, Tony DeRose, Joe D.

Warren: Multiresolution Analysis for Surfaces of Arbitrary Topological Type. ...

www.informatik.uni-trier.de/~ley/db/ indices/a-tree/d/DeRose:Tony.html - 10k - [Cached](#) - [Similar pages](#)[[More results from www.informatik.uni-trier.de](#)]**Search Result for Michael Lounsbery**Search Result for **Michael Lounsbery**. ... Matthias Eck, Tony DeRose, Tom Duchamp,Hugues Hoppe, **Michael Lounsbery**, and Werner Stuetzle. Technical Report... ...hpsearch.uni-trier.de/hp/a-tree/ l/Lounsbery:Michael.html - 8k - [Cached](#) - [Similar pages](#)**Smith College Theatre Department: Michael J. Lounsbery Jr.****Michael J. Lounsbery Jr.** Lighting Supervisor. ... **Michael Lounsbery** (Lighting Supervisor)

holds an MFA in Light and Sound Design from the University of Memphis. ...

www.smith.edu/theater/faculty/lounsbery.html - 5k - [Cached](#) - [Similar pages](#)**Multiresolution Analysis of Arbitrary Meshes - Eck, DeRose, Hoppe ...**... 1995) (Make Corrections) (237 citations) Matthias Eck, Tony DeRose, Tom Duchamp, Hugues Hoppe, **Michael Lounsbery**, Werner Stuetzle Computer Graphics Home/Search ...citeseer.nj.nec.com/eck95multiresolution.html - 26k - [Cached](#) - [Similar pages](#)**Multiresolution Analysis for Surfaces of Arbitrary Topological ...**

Multiresolution Analysis for Surfaces of Arbitrary Topological Type (1994) (Make

Corrections) (127 citations) **Michael Lounsbery**, Tony D. DeRose, Joe Warren ACM ...citeseer.ist.psu.edu/188531.html - 25k - [Cached](#) - [Similar pages](#)**[PDF] Wavelets**

09/515, 517

[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

michael lounsbery path vertex face

Google Search

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)Searched the web for **michael lounsbery path vertex face**. Results 1 - 10 of about 59. Search took 0.30 seconds.**Michael - Buy Books and More on eBay**

Sponsored Link

www.eBay.com eBay - The World's Online Marketplace**[PS] www.stat.washington.edu/wxs/Tiling/tiling.ps.gz**File Format: Adobe PostScript - [View as Text](#)... is then a multi-source shortest **path** problem, which is ... **VERTEX-BASED TRIANGULATION OF MESHES 7**. ... DeRose, Tom Duchamp, Hugues Hoppe, **Michael Lounsbery**, and Werner ...[Similar pages](#)**[PS] www.cgl.uwaterloo.ca/~smann/Papers/spie90.ps**File Format: Adobe PostScript - [View as Text](#)... 1. **Michael Lounsbery**, Charles Loop, Stephen Mann, David Meyers, ... to walk along a user-specified **path** through the ... Each **vertex** of the mesh has an associated dstruct ...[Similar pages](#)**[CIS881 Schedule](#)**... Lofting: acceptable surface as **path** through grid of **vertex** pairs, global ... Eck, Tony DeRose, Tom Duchamp, Hugues Hoppe, **Michael Lounsbery**, Wener Stuetzle ...www.cis.ohio-state.edu/~parent/classes/784/scheduleS99.html - 11k - [Cached](#) - [Similar pages](#)**[PDF] [Three-dimensional Geometric Metamorphosis based on Harmonic Maps](#)**File Format: PDF/Adobe Acrobat - [View as HTML](#)... These 2D embeddings, called H_1 and H_2 , have the same connectivity (we use a word connectivity to denote a **vertex/edge/face** graph of a polygon) as M_1 and M_2 ...web.sfc.keio.ac.jp/~kanai/papers/tvc98morph.pdf - [Similar pages](#)**[PDF] [Multiresolution Analysis of Arbitrary Meshes](#)**File Format: PDF/Adobe Acrobat - [View as HTML](#)... DeRose Tom Duchamp Hugues Hoppe y **Michael Lounsbery** z Werner ... could be used in place of **Lounsbery** et al. ... diagram is a multi-source shortest **path** problem in ...research.microsoft.com/~hoppe/mra.pdf - [Similar pages](#)**[PDF] [Multiresolution Analysis of Arbitrary Meshes](#)**

File Format: PDF/Adobe Acrobat

... DeRose Tom Duchamp Hugues Hoppe y **Michael Lounsbery** z Werner ... 18] could be used in place of **Lounsbery** et al ... called the base complex, with a **face** corresponding to ...delivery.acm.org/10.1145/220000/218440/p173-eck.pdf?key1=218440&key2=9062888301&coll=GUIDE&dl...[Similar pages](#)**[PDF] [Polygonal Simplification: An Overview](#)**File Format: PDF/Adobe Acrobat - [View as HTML](#)... To trace a **path** around the boundary of a ... Eck, Tony DeRose, Tom Duchamp, Hugues Hoppe, **Michael Lounsbery**, and Werner ... a final weighting for each **vertex** using a ...www.cs.unc.edu/~eriksonc/Research/Paper/SimpOverview/SimpOverview.pdf - [Similar pages](#)**[PDF] [Multiresolution Analysis of Arbitrary Meshes Abstract](#)**File Format: PDF/Adobe Acrobat - [View as HTML](#)... Tony DeRose Tom Duchamp Hugues Hoppe y **Michael Lounsbery** z Werner ... reproduce here all

[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

michael lounsbery face identifier

Google Search

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)Searched the web for michael lounsbery face identifier. Results 1 - 10 of about 26. Search took 0.33 seconds.**Michael - Buy Books and More on eBay**

Sponsored Link

www.eBay.com eBay - The World's Online Marketplace

[PDF]Interactive Multiresolution Surface Viewing

File Format: PDF/Adobe Acrobat

... vertices of M J . We next apply the filter bank analysis algorithm of **Lounsbery** etal. ... Each leaf of Q corresponds to a **face** of M J . This tree organization was ...

delivery.acm.org/10.1145/240000/237213/ p91-certain.pdf?key1=237213&key2=1207909301&coll=portal&am... -

[Similar pages](#)**[PDF]Progressive Meshes**

File Format: PDF/Adobe Acrobat

... A common discrete attribute, the material **identifier**, determines the shader function used in rendering a **face** of the mesh [18]. ...

delivery.acm.org/10.1145/240000/237216/

p99-hoppe.pdf?key1=237216&key2=1692688301&coll=portal&... - [Similar pages](#)**[PDF]Truly Selective Refinement of Progressive Meshes**File Format: PDF/Adobe Acrobat - [View as HTML](#)... Various simplification operators have been introduced, such as vertex unification, vertex removal & retriangulation, edge collapse, and **face** collapse. ...www.samsung.com/AboutSAMSUNG/SocialCommitment/ HumantechThesis/downloads/7th/55.pdf - [Similar pages](#)**[PDF]Simplification Culling of Static and Dynamic Scene Graphs**File Format: PDF/Adobe Acrobat - [View as HTML](#)... a part of that grid's model, as well as the vertices making up that **face**. ... vertex is in a different partition, we union this partition's **identifier** with a ...www.cs.unc.edu/~geom/HLOD/SimpCull/SimpCull.pdf - [Similar pages](#)**[PDF]A Framework for the Real-Time Walkthrough of Massive Models**File Format: PDF/Adobe Acrobat - [View as HTML](#)... During preprocessing, color and depth information (MxN pixels) are stored for each textured cull box **face**. Each **face** is then converted ...www.cs.unc.edu/~hoff/papers/mmr/i3d99.pdf - [Similar pages](#)**3D Computer Graphics :: Levels of Detail & Polygonal ...**... **Face** normal Simplification : all adjacent faces with near-parallel ... M., DeRose, T., Duchamp, T., Hoppe, H., **Lounsbery**, M., and ... Email: **Michael.Krus@der.edfgdf.fr** ...mkrus.free.fr/CG/LODS/xrds/ - 46k - [Cached](#) - [Similar pages](#)**[PDF]Compressing isosurfaces generated with marching cubes**File Format: PDF/Adobe Acrobat - [View as HTML](#)... 1995; Heinrich and **Michael** 1993; Hoppe et al ... Visual Computer (2002) 18:54-67 Digital Object **Identifier** (DOI) 10.1007 ... 2). Two cubes are **face** (or edge, or vertex ...cgvr.korea.ac.kr/Seminar/2002/src/PA-02-25.pdf - [Similar pages](#)**Listes De Films Divx et Resumer - [Translate this page]**... LA REINE DES DAMNES Réalisateur : **Michael** Rymer Année ... créature capable de faire

face au roi ... Réalisateur : Art Stevens, John **Lounsbery**, Wolfgang Reitherman ...
membres.lycos.fr/titoumdivx/photoalbum.html - 101k - [Cached](#) - [Similar pages](#)

[PDF] [The Randomized Sample Tree: A Data Structure for Interactive ...](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Stored Virtual Environments Jan Klein * Jens Krokowski * Matthias Fischer *

Michael Wand † Rolf ... and let $A(B(u))$ denote the area of one side **face** of the ...

www.upb.de/cs/ag-madh/PapersPostscript/p94-klein.pdf - [Similar pages](#)

[PDF] [FRENCH-AMERICAN FOUNDATION FRENCH-AMERICAN FOUNDATION](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... des voyages d'étude, afin d'**identifier**, d'examiner ... funds and launching, in
the **face** of some ... **Michael** Iovenko (1995-2001) carried the Foundation through ...

www.frenchamerican.org/pubs/FAFAnnualReport2001-2.pdf - [Similar pages](#)

Google ►

Result Page: 1 2 [Next](#)

[Search within results](#)

Dissatisfied with your search results? [Help us improve.](#)

[Google Home](#) - [Advertise with Us](#) - [Business Solutions](#) - [Services & Tools](#) - [Jobs, Press, & Help](#)

©2003 Google

[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

unique face identification polygon mesh

Google Search

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)Searched the web for **unique face identification polygon mesh**. Results 1 - 10 of about 618. Search took 0.15 sec**[PDF]M 5.3 Fact Sheet**File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Symbolic Math, System **Identification**, Wavelet M ... shift Set operators Union, **unique**, intersection, difference ... properties Vectorized patch, **face** coloring, edge ...
www.serc.iisc.ernet.in/facilities/software/matlab_downloads/9319v01.matlab5.3.pdf - [Similar pages](#)

Sponsored Links

Free Dense 3D Data Viewer
 View, Measure, Compress & Publish
 3D Data Sets with RapidForm Basis
www.rapidform.com
 Interest: ...

[See your message here...](#)**Citations: An Introduction to Solid Modeling - Mantyla (...**

... vectors, only two (independent but not **unique**) Euler operators ... as a pair and a **polygon** as a ... 4. **FACE IDENTIFICATION METHOD FOR MANIFOLD OBJECTS OF GENUS ZERO** ...
citeseer.nj.nec.com/context/111594/0 - 35k - [Cached](#) - [Similar pages](#)

[PDF]Human body 3D imaging by speckle texture projection ...File Format: PDF/Adobe Acrobat - [View as HTML](#)

... ensuring that there is always a **unique** pattern on ... a 3D **face** model implicitly encodes many 2D **face** poses and ... better assist a witness in the **identification** of a ...
faraday.dcs.gla.ac.uk/people/sjm/papers/sens_rev_article.pdf - [Similar pages](#)

[PDF]Object identification in compressed view-dependent ...File Format: PDF/Adobe Acrobat - [View as HTML](#)

... vertex-related Figure 3: Propagation of **face**- and vertex ... of the scene hierarchy a **unique** integer identifier ... our main goal is object **identification** as described ...
www.icg.tu-graz.ac.at/Grabner:2003:OIC/objectid.pdf - [Similar pages](#)

[PDF]MATLAB 6-for numeric computation, visualization, algorithm ...File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Statistics, Symbolic Math, System **Identification**, Wavelet M ... Set operators Union, **unique**, intersection, difference ... properties Vectorized patch, **face** coloring and ...
www.comsol.se/shared/downloads/docs/matlab/MATLAB65.pdf - [Similar pages](#)

[PDF]MSC.Patran

File Format: PDF/Adobe Acrobat

... **face** skew, **face** taper, **face** warp, tet ... selected node or element – **Identification** of minimum ... and thickness – Fifteen **unique identification** symbols • Axes ...
www.mscsoftware.com/assets/1890_P3203ZZZLT.DAT.pdf - [Similar pages](#)

[PDF]GEOMARK – Watermarking of Geometrical DataFile Format: PDF/Adobe Acrobat - [View as HTML](#)

... secret information strings, for example **identification** numbers. ... There is no **unique** representation ... in the **mesh**, thus altering adjacent **face** (triangle) normals ...
www.inigraphics.net/publications/topics/1999/issue1/1_99a04.pdf - [Similar pages](#)

[PDF]Exploring Surface Characteristics with Interactive Gaussian ...

File Format: PDF/Adobe Acrobat

... For object **identification** Ikeuchi and Hebert use the observed EGI ... fast the normal of the sur- **face** is changing ... For each **unique** edge, the Gaussian image is taken ...
delivery.acm.org/10.1145/610000/602196/p553-lowekamp.pdf?key1=602196&key2=9241360501&coll=ACM&... - [Similar pages](#)

[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

base mesh polygon

Google Search

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)Searched the web for **base mesh polygon**.

Results 1 - 10 of about 9,040. Search took 0.15 seconds.

Rorshachs Journal - Pixel Herding & Polygon Sodomising since '95

... After I've check the back of the model I can take it into Photoshop and starting shading some muscle tones in greyscale over the **base mesh** that I've coloured. ...
www.planetquake.com/polycount/cottages/rorshach/help/helpq2new.htm - 13k -
[Cached](#) - [Similar pages](#)

Sponsored Links

Free Dense 3D Data Viewer
 View, Measure, Compress & Publish
 3D Data Sets with RapidForm Basis
www.rapidform.com
 Interest: ☐ [View](#)

[See your message here...](#)

3D Tutorials : 3D Studio Max

... This tutorial will show **polygon** reduction techniques. ... Workflow Sequence. Drawing setup
 - Arrange your scanned character design for modeling; Creating a **base mesh**; ...
www.3dlinks.com/tutorials/max/max_tutorials.cfm?tutorial=lpindex - 21k - [Cached](#) - [Similar pages](#)

[PDF]OpenMesh – a generic and efficient polygon mesh data structure

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... half-edge, an incident vertex and an incident **polygon**. ... algorithms operating on all
 of these **mesh** types, we ... all meshes from a common virtual **base** class, or do ...
www.opensg.org/OpenSGPLUS/symposium/Papers2002/Botsch_OpenMesh.pdf - [Similar pages](#)

Page P003.html

... Here we have an example of wavelet analysis of a **polygon mesh**. ... Then we can, if we
 want, create different resolution models by taking the **base mesh**, and, for ...
graphics.stanford.edu/~kapu/wave/slides/P003.html - 2k - [Cached](#) - [Similar pages](#)

[PPT]www-dsp.rice.edu/~lavu/research/doc/mslavu.ppt

File Format: Microsoft Powerpoint 97 - [View as HTML](#)

... Results. 3D geometry data. Geometry. **Polygon** meshes. Geometry & connectivity. Geometry. ... Multilevel
 representation. **Base mesh**. Successively refine the **mesh**: Subdivision. ...
[Similar pages](#)

List of Figures

... vertices and four faces have been added (d) The **base mesh** after three ... Applying **polygon**
 limitations ... The **mesh** on the left was constructed with a **polygon** limit of ...
www.cs.uct.ac.za/Research/CVC/projects/mesh/main/node2.html - 9k - [Cached](#) - [Similar pages](#)

Intel Corporation - Research and Development, Media and Graphics ...

... color is the product of the **base** color multiplied ... highlight texels increases the highlight
 area on the **mesh**. ... Hidden Line style fills the **polygon mesh** with the ...
www.intel.com/labs/media/3dsoftware/nonphoto.htm - 34k - [Cached](#) - [Similar pages](#)

Julian's CG site

... I will also be uploading the **base mesh** in stages up to a certain point, this ... of course
 many different ways, I always start mine with a single **polygon** using the ...
www.cg-art.i12.com/mad_2.html - 27k - [Cached](#) - [Similar pages](#)

Web Server: Chapter 6 Modeling Shapes with Polygonal Meshes

... **Mesh(polygon p)** { ... Number vertices in the **base** 0, ..., N-1 Number vertices
 in the cap N, ..., 2N - 1 (edge joins vertices i and i & N) Vertex list: (x i ...
www.eng.mu.edu/corlissg/151.02Su/ch6_mesh.html - 25k - [Cached](#) - [Similar pages](#)

[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

polygon mesh data structure

Google Search

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)Searched the web for **polygon mesh data structure** . Results 1 - 10 of about 10,800. Search took 0.19 seconds.

Polygon mesh data structure

Polygon Mesh Data Structure for 3D Graphics. Introduction. The **polygon mesh data****structure** is the most common and oldest modeling method for computer graphics. ...www.siggraph.org/education/materials/HyperGraph/[modeling/polymesh/polymesh.htm](#) - 7k - [Cached](#) - [Similar pages](#)

Sponsored Links

Free Dense 3D Data Viewer
 View, Measure, Compress & Publish
 3D Data Sets with RapidForm Basis
www.rapidform.com
 Interest:

[See your message here...](#)

[PDF]OpenMesh – a generic and efficient polygon mesh data structure

File Format: PDF/Adobe Acrobat - [View as HTML](#)OpenMesh – a generic and efficient **polygon mesh data structure** M. Botsch S. Steinberg

S. Bischoff L. Kobbelt Lehrstuhl für Informatik VIII Computergraphik ...

www.opensg.org/OpenSGPLUS/symposium/Papers2002/Botsch_OpenMesh.pdf - [Similar pages](#)

Polygon mesh data structure

Polygon Mesh Data Structure for 3D Graphics. Look at a 3D cube in a right-handed coordinate system. One Possible **Data Structure**: Point3D ...www.udayton.edu/~cps/cps560/siggraph/hypgraph/modeling/polymesh/polymesh.htm - 6k - [Cached](#) - [Similar pages](#)

Polygon mesh data structure

Polygon Mesh Data Structure for 3D Graphics. One Possible **Data Structure**:

Point3D = record x, y, z : real; end ; Figure = array (1 ...

cs.sungshin.ac.kr/~hkim/LECTURE/CG/polymesh.htm - 5k - [Cached](#) - [Similar pages](#)

flipCode - Tutorial - The Half-Edge Data Structure

... These properties make the half-edge **data structure** an excellent choice for many applications ... For the purpose of a **polygon mesh**, this means that every edge is ...www.flipcode.com/tutorials/tut_halfedge.shtml - 25k - [Cached](#) - [Similar pages](#)

1B) Polygon mesh management

... The above diagram shows just one possible implementation of a **polygon mesh data structure**. FvDFH section 12.5.2 describes another ...www.cl.cam.ac.uk/Teaching/1998/AGraphics/11b.html - 10k - [Cached](#) - [Similar pages](#)

How to use the mesh structure

... 50 // total of the generators here for a **mesh** of 2500 ... Once the **data** are loaded, it is very simple to plot ... the vertices adherent to the cell begin **polygon[y].x** ...www.uni-bayreuth.de/departments/philosophie/deutsch/TheLab/IrregularCA/howtouse.htm - 13k - [Cached](#) - [Similar pages](#)

[PPT]Out-of-Core Compression for Gigantic Polygon Meshes

File Format: Microsoft Powerpoint 97 - [View as HTML](#)Out-of-Core Compression for Gigantic **Polygon Meshes**. Martin Isenburg, StefanGumhold. ... New out-of-core **mesh data structure**. Efficient building process. ...www.cs.northwestern.edu/~pren/slides/out-of-core_compression.ppt - [Similar pages](#)

Lattice Proposal

... The Lattice **structure** is composed of free-form surface and simple **polygon mesh**.

[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

polygon unique face identifier

Google Search

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)Searched the web for **polygon unique face identifier**. Results 1 - 10 of about 1,850. Search took 0.26 seconds.

THE NATIONAL MAPPING AGENCIES OF BRITAIN & IRELAND

... normally in terms of type or use: for example, a **polygon** feature could ... An **identifier** that is primarily intended to provide **unique** and unambiguous feature ... **Face**. ...

www.osmaps.org/glossary.htm - 27k - [Cached](#) - [Similar pages](#)

DCMI Box Encoding Scheme

... a **unique** geocode, such as a postal code; the ... Alternatively, another notation describing a **polygon** or polyhedron may ... coordinate for the northernmost **face** or edge ...

dublincore.org/documents/2000/07/28/dcmi-box/ - 23k - [Cached](#) - [Similar pages](#)

Assignment 7 BSP Hidden Surface Removal Algorithm

... GLIDE 3.0 format to stdout with the **polygon** faces included in ... a file, the id values are assumed **unique** for each ... must have a different id, but a **face** could have ...

www.cs.berkeley.edu/~ddgarcia/cs184/h7/ - 15k - [Cached](#) - [Similar pages](#)

Classic Routines

... If you delete point #1 and point #2 from a **polygon**, the next ... key long The **unique identifier** returned by ... offset integer Number of the **face** in the original shell ...

www.maths.tcd.ie/~gavin/Manual/ce.htm - 50k - [Cached](#) - [Similar pages](#)

legal survey area

... For example, a **polygon** can be bounded by ... the outer boundary of an earth surface **face**. ... legal_survey_point **unique** list[0 .. N] of (legal_survey_point) Indicates ...

www.august.com/epicentre/inherit/legal_survey_area.html - 16k - [Cached](#) - [Similar pages](#)

[RTF] ***** ...

File Format: Rich Text Format - [View as HTML](#)

... ufi 6, 6,i - **unique** feature **identifier**. ... units are coded by the unit item in the **polygon** attribute. ... with the codes used matching the nomenclature on the map **face**: ...

www.georeality.com.au:81/biab/Metadata/geology/mur_250/Geology_amd.rtf - [Similar pages](#)

TXT2PCX.COM Is a **unique**, memory resident, file utility which will ...

Oktalyzer Formats

myfileformats.com/index.php/c-functions/packet/.reg/bank.html - 7k - [Cached](#) - [Similar pages](#)

The PLY **Polygon** File Format

AVI File format

myfileformats.com/index.php/tif/general/cookie/isff.html - 7k - [Cached](#) - [Similar pages](#)

[[More results from myfileformats.com](#)]

[PPT] RASTER VECTOR

File Format: Microsoft Powerpoint 97 - [View as HTML](#)

... used for mapping and analyzing things that exist and events that happen on the **face** of the ... 1. Digitize a **unique** text entity within each **polygon** area. ...

www.geology.fau.edu/course_info/spring02/geo4151/gistopic7students.ppt - [Similar pages](#)

[PDF] OpenMesh – a generic and efficient **polygon** mesh data structure

File Format: PDF/Adobe Acrobat - [View as HTML](#)

[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

polygon face path

Google Search

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)Searched the web for **polygon face path**.

Results 1 - 10 of about 16,000. Search took 0.16 seconds.

[vtkusers] Contouring **polygon** & outline **path**

... FONT **face**=3DArial size=3D2>For modeling operation, I have to take = an outline=20 and expand it while moving it along a **path** (concave and convexe = **polygon**). ...
 public.kitware.com/pipermail/vtkusers/ 2002-October/014017.html - 6k - [Cached](#) - [Similar pages](#)

www-svg@w3.org from March 2003: Re: Updated test suite?

... animateTransform | g | defs | use | switch | image | **path** | rect | circle |line
 | ellipse | polyline | **polygon** | text | a | font | font-face)*, got (style ...
 lists.w3.org/Archives/Public/www-svg/2003Mar/0046.html - 9k - [Cached](#) - [Similar pages](#)

An Optimal Data Structure for Shortest Rectilinear **Path** Queries ...

... the Largest Axis-Aligned Rectangle in a **Polygon** in - Ralph Boland Jorge (Correct)
 On Geometric **Path** Query Problems ... Segmentation of a Head into **Face**, Ears, Neck ...
 citeseer.nj.nec.com/400327.html - 25k - [Cached](#) - [Similar pages](#)

Attribute Index - SVG 1.1 - 20020215

... altGlyphItem, font-**face**-src, metadata, svg, g, defs, desc, title, symbol, use, image,
 switch, style, **path**, rect, circle, ellipse, line, polyline, **polygon**, text ...
 www.w3.org/TR/2002/WD-SVG11-20020215/attindex.html - 101k - [Cached](#) - [Similar pages](#)

WebWorlds: Polygons, Sweeping, Tipping and Lathing

... Tip - This tool sweeps a selected **polygon**, **face**, or group of faces to a point ... Lathe
 - This tool sweeps a shape along a modifiable circular or spiral **path**. ...
 www.msu.edu/user/ionescua/pioneer/cpwk2_4.htm - 6k - [Cached](#) - [Similar pages](#)

A **face** for a robot: The **path** to creating a **face** to socially ...

A **face** for a robot: The **path** to creating a ... a flip-pack animation of the **face** opening
 and ... by 1974, Parke used Henri Gouraud's smooth **polygon** shading algorithm ...
 www.its.caltech.edu/~vikram/cs286/report/ - 101k - [Cached](#) - [Similar pages](#)

MEL How-To

... How do I determine the **path** for a script while it is executing; for example, to
 load another file in the ... How do I get the normal vector for a **polygon face**? ...
 www.ewertb.com/maya/mel/ - 16k - [Cached](#) - [Similar pages](#)

Conformance

... Verbose level = 2. Random number seed = 1. **Path** inactive. Visual Report. Display
 ID = 35. ... Quad Rasterization test passed. **Polygon Face** test passed. ...
 www.mesa3d.org/conform.html - 19k - [Cached](#) - [Similar pages](#)

Maya Mel Scripts, MAYA Mel Scripts, MEL, Scripts for Maya

... This script simulates subdivision modeling with existing Maya Complete **polygon** tools. ... **Face**
Path Selection Tool v1.0.: [By Andras POLONYI] - [Works on: 3.x ...
 www.highend3d.com/maya/mel/ ?group=melscripts§ion=polygon - 101k - [Cached](#) - [Similar pages](#)

[poc]PolarEyez is a new focus+context visualization for ...

File Format: Microsoft Word 2000 - [View as HTML](#)

... Figure 3.5: Rays are (a) grouped by **face**, and (b) ordered within a **face** by a scan-line

path. ... Hyper-cube maps to a **polygon** with equal sides and angles (black ...
infovis.cs.vt.edu/multid/thesis%20writeup/CHAP3.doc - [Similar pages](#)

Goooooooooooooogle ►
Result Page: 1 2 3 4 5 6 7 8 9 10 **[Next](#)**

[Search within results](#)

Dissatisfied with your search results? [Help us improve.](#)

[Google Home](#) - [Advertise with Us](#) - [Business Solutions](#) - [Services & Tools](#) - [Jobs, Press, & Help](#)

©2003 Google

[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

catmul clark

Google Search

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)Searched the web for **catmul clark**.

Results 1 - 10 of about 49. Search took 0.17 seconds.

Did you mean: **catmull** clark**Multiresolution Wavelet Representations for Arbitrary Meshes (...**

... Singularity detection and processing with wavelets - Mallat, Hwang - 1992 160 spline surfaces on arbitrary topological meshes (context) - **Catmul, Clark** et al. ...
 citeseer.nj.nec.com/natsev97multiresolution.html - 25k - [Cached](#) - [Similar pages](#)

[PPT]TitleFile Format: Microsoft Powerpoint 97 - [View as HTML](#)

... topologically restricted. **Catmul/Clark** Subdivision. Why? ... Generalization of **Catmul/Clark**: semi-sharp features controlled by edge sharpness s. Hybrid Subdivision: ...
 www.cs.berkeley.edu/~j-yen/cs285/derose.ppt - [Similar pages](#)

Untitled

... The scheme to implement may be Loop subdivision surfaces or **Catmul-Clark** subdivision surfaces with a meaningfull user interface. ...

www.cs.bilkent.edu.tr/~gudukbay/cs466/ project_list/project_list.html - 6k - [Cached](#) - [Similar pages](#)

[PPT]kopernik.cc.fmph.uniba.sk/~leskovsky/SubdivSurf.pptFile Format: Microsoft Powerpoint 97 - [View as HTML](#)

... . * . * . Midedge. C1. * . * . Doo-Sabin. C1. * . * . Kobbelt. C2/C1. * . * . **Catmul-Clark**. C1. * . * . Butterfly. C2/C1. * . * . Loop. Smoothness. Vertex split. Face split. Triangle. Quad. ...

[Similar pages](#)

Who needs Bryce, Use Blender... - Open 3D Forum

... the name says it all, note I heard ball-joint IKA is being released on the next update, it already supports **catmul-clark** patches (aka MetaNURBS) a decimator ...

www.designcommunity.com/messages/9359.html - 7k - [Cached](#) - [Similar pages](#)

Caltech Computer Science Technical Reports - Is this a ...

... Extensions to other popular uniform primal subdivision schemes such as **Catmul-Clark**, and dual schemes such as Doo-Sabin, are relatively straightforward but will ...

caltechcstr.library.caltech.edu/archive/00000171/ - 7k - [Cached](#) - [Similar pages](#)

Character Modeling: Chapter 1

... I used a subdivision mesh (old s-mesh) to smooth out the model, but you could also use a plain mesh with(out) smooth rendering, **catmul-clark** (now in Blender ...

neenjatech.org/projects/character/body/page1.html - 4k - [Cached](#) - [Similar pages](#)

:: El Portal del 3D y la Animación :: 3DyAnimacion.com

... best ones. To be more specific, polygons used with Subdivision Surfaces technique (like **Catmul-Clark** in RenderMan). The NURBS are ...

www.3dyanimacion.com/entrevistas/ entrevistas.cfm?link=fcortinaeng - 44k - [Cached](#) - [Similar pages](#)

[[More results from www.3dyanimacion.com](#)]

Subdivision Surfaces

... I hope to add a **Catmul/Clark** filter by the end of the year. There are

several examples in graphics/examplesTcl to illustrate the filters. ...

public.kitware.com/pipermail/vtkusers/ 1999-October/002473.html - 4k - [Cached](#) - [Similar pages](#)

[forcefield gallery](#)

... I have some normals issues with the s-meshes (I might just subdivide and smooth them myself, or try that **catmul-clark** plugin...) posted by chris hillman at 12.2 ...

forcefield.tripod.com/gallery.html - 7k - [Cached](#) - [Similar pages](#)

Did you mean to search for: [catmull clark](#)

Goooooogle ►

Result Page: 1 2 3 4 5 [Next](#)

[Search within results](#)

Dissatisfied with your search results? [Help us improve.](#)

[Google Home](#) - [Advertise with Us](#) - [Business Solutions](#) - [Services & Tools](#) - [Jobs, Press, & Help](#)

©2003 Google


[Advanced Search](#) [Preferences](#) [Language Tools](#) [Search Tips](#)

catmul clark data structure

Google Search

[Web](#) [Images](#) [Groups](#) [Directory](#) [News](#)
Searched the web for **catmul clark data structure**.

Results 1 - 8 of about 9. Search took 0.24 seconds.

Try [Google Answers](#) to get help from expert researchers.Did you mean: [catmull](#) clark data structure[\[PPT\]](#) [kopernik.cc.fmph.uniba.sk/~leskovsky/SubdivSurfEn.ppt](#)File Format: Microsoft Powerpoint 97 - [View as HTML](#)... . *. *. **Catmul-Clark**. C1. *. *. *. ... Used technology. **Data structures**. The implementation of the subdivision schemes. ... The use in commercial software. The **Structure**. Input: ...[Similar pages](#)[\[PDF\]](#) [IBM Research Report](#)File Format: PDF/Adobe Acrobat - [View as HTML](#)... to other popular uni- form primal subdivision schemes such as **Catmul-Clark**, and dual ... An algorithm based on Tarjan's fast union-find **data structure** [9] can be ...[researchweb.watson.ibm.com/people/t/taubin/pdfs/Taubin-ibm21880.pdf](#) - [Similar pages](#)[Enseignements -Troisième année - Images et réalités ...](#) - [[Translate this page](#)]... Clustering / **data mining**; **Data structure**. Examination. Written exam. ... B-rep **data structures**. ... Subdivision surfaces: **Catmul-Clark**, Butterfly and Loop's scheme. ...[www-ensimag.imag.fr/formations/enseignements/3e-annee/im-rv.html](#) - 54k - [Cached](#) - [Similar pages](#)[Enseignements -Troisième année - Images et réalités ...](#) - [[Translate this page](#)]... Clustering / **data mining**; **Data structure**. ... diagram, meshes, mesh implication, B-rep **data structures** ... Subdivision surfaces: **Catmul-Clark**, Butterfly and Loop's scheme ...[www-ensimag.imag.fr/formations/enseignements/3e-annee/2001-2002/im-rv.html](#) - 41k - [Cached](#) -[Similar pages](#)[\[PS\]](#) [caltechcstr.library.caltech.edu/archive/00000171/00/postscript.ps](#)File Format: Adobe PostScript - [View as Text](#)... to other popular uniform primal subdivision schemes such as **Catmul-Clark**, and dual schemes ... An algorithm based on Tarjan's fast union-find **data structure** [9] can ...[Similar pages](#)[\[PDF\]](#) [Is This A Quadrisected Mesh ?](#)File Format: PDF/Adobe Acrobat - [View as HTML](#)... to other popular uni- form primal subdivision schemes such as **Catmul-Clark**, and dual ... An algorithm based on Tarjan's fast union-find **data structure** [9] can ...[caltechcstr.library.caltech.edu/archive/00000171/01/postscript.pdf](#) - [Similar pages](#)

BIBLIOGRAPHY

... Background on Smooth Surfaces. E. **Catmul** and J. **Clark**: "Recursively generated B-spline surfaces ... - Effective display of complex **data** using just two dimensions. ...[www.cs.berkeley.edu/~sequin/CS285/bibl.html](#) - 11k - [Cached](#) - [Similar pages](#)[Programming question for Bjorn - www.ezboard.com](#)... Where did you go to learn about the wing-edge **data structure** and all the ... d part I can answer that one he didnt wings uses **catmul-clark** subdivision algorithms ...[pub33.ezboard.com/fnendowingsmiraifrm8.showMessage?topicID=168.topic](#) - 22k - [Cached](#) - [Similar pages](#)

L Number	Hits	Search Text	DB	Time stamp
-	25	lounsbery	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 12:50
-	1	(polygon\$3 or mesh) with level with path with vertex	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 12:53
-	156	(polygon\$3 or mesh) near2 data near structure	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 12:53
-	0	((polygon\$3 or mesh) near2 data near structure) same (face or patch) near identif\$6	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 12:54
-	0	((polygon\$3 or mesh) near2 data near structure) same (face or patch) same path same level same vertex	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 12:55
-	27	((polygon\$3 or mesh) near2 data near structure) same (face or patch)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 12:54
-	21	((polygon\$3 or mesh) near2 data near structure) and base near (polygon or mesh or patch)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 12:58
-	1	base near (polygon or mesh or patch) same path near (mesh or patch)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 12:59
-	0	catmul near clark	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 12:59
-	20	catmul\$clark	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:05
-	828	(polygon or mesh) and (face or patch) and level and path and vertex	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:05
-	13	(polygon or mesh) and (face or patch) and (level same path same vertex)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:12
-	8	(polygon or mesh) and base near (face or patch) and (face or patch) near path	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:13
-	0	base near (face or patch) near identifier	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:14

-	21626	base near (face or patch)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:14
-	60	base near (face or patch) with identif\$6	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:14
-	12	(base near (face or patch) with identif\$6) and polygon	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:17
-	15	("4618924" "4752352" "4789931" "4837703" "4863538" "4866631" "4907164" "4938816" "4944817" "4949270" "4961041" "4996010" "5017753" "5053090" "5432704").PN.	USPAT	2003/08/12 13:16
-	134	(quadtree or octree) with data near structure	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:19
-	28	((quadtree or octree) with data near structure) same tree	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:18
-	1	((quadtree or octree) with data near structure) same tree) same vertex	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:18
-	92	(quadtree or octree) near2 data near structure	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:31
-	58	(polygon or mesh) same (patch or face) same path same level	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:32
-	3	((polygon or mesh) same (patch or face) same path same level) and unique	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:33
-	6	unique near (face or patch) near identif\$6	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:34
-	1085	(face or patch) near identif\$6	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:34
-	411263	((face or patch) near identif\$6) smae (polygon or mesh)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:35
-	34	((face or patch) near identif\$6) same (polygon or mesh)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:42

-	623	(polygon or mesh) same (file or data) near structure	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:43
-	0	((polygon or mesh) same (file or data) near structure) and (patch or face) near name	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:43
-	292	(patch or face) near name	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:43
-	0	((patch or face) near name) same (polygon or mesh)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:43
-	52	(polygon or mesh) same (face or patch) with (file or data) near structure	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:55
-	0	((polygon or mesh) same (face or patch) with (file or data) near structure) and base near face	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:45
-	0	((polygon or mesh) same (face or patch) with (file or data) near structure) and base near patch	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:45
-	0	((polygon or mesh) same (face or patch) with (file or data) near structure) and base near polygon	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2003/08/12 13:45
-	469	(382/154).CCLS.	USPAT	2003/08/12 13:45
-	91	((382/154).CCLS.) and (polygon or mesh)	USPAT	2003/08/12 13:45
-	56	((382/154).CCLS.) and (polygon or mesh) and level	USPAT	2003/08/12 13:46
-	63	((382/154).CCLS.) and (polygon or mesh) and base	USPAT	2003/08/12 13:46
-	3	((382/154).CCLS.) and (polygon or mesh) and base near (patch or mesh)	USPAT	2003/08/12 13:47
-	0	(polygon or mesh) and subdiv\$6 and base near (mesh or polygon or face or patch or facet)	USPAT	2003/08/12 13:48
-	2369	(polygon or mesh) and subdiv\$6 and (face or patch or facet)	USPAT	2003/08/12 13:48
-	96	(polygon or mesh) near2 subdiv\$6 and (face or patch or facet)	USPAT	2003/08/12 13:48
-	42	(polygon or mesh) near2 subdiv\$6 same (face or patch or facet)	USPAT	2003/08/12 13:52
-	424	(polygon or mesh) and path near2 (face or facet or patch)	USPAT	2003/08/12 13:53
-	244	((polygon or mesh) and path near2 (face or facet or patch)) and base	USPAT	2003/08/12 13:53
-	22	(polygon or mesh) and path near2 (face or facet or patch) same base	USPAT	2003/08/12 13:53
-	53	(polygon or mesh) same path near2 (face or facet or patch)	USPAT	2003/08/12 13:54
-	1476	"59" and vertex and level and base	USPAT	2003/08/12 13:54
-	0	((polygon or mesh) same path near2 (face or facet or patch)) and vertex and level and base	USPAT	2003/08/12 13:54
-	0	((polygon or mesh) same path near2 (face or facet or patch)) and vertex and level	USPAT	2003/08/12 13:54
-	22	(polygon or mesh) with path near2 (face or facet or patch)	USPAT	2003/08/12 13:55

-	0	((382/154).CCLS.) and path near (face or facet or patch)	USPAT	2003/08/12 13:55
-	23	((382/154).CCLS.) and path	USPAT	2003/08/12 13:55
-	0	path with (polygon or mesh) with (face or patch) same (file or data) near structure	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2003/08/12 13:56
-	18	((polygon or mesh) same (file or data) near structure) same path	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2003/08/12 14:02
-	2959	(345/419-428).CCLS.	USPAT	2003/08/12 14:02
-	471	((345/419-428).CCLS.) and (mesh or polygon\$4).ab.	USPAT	2003/08/12 14:02
-	73	((345/419-428).CCLS.) and (mesh or polygon\$4).ab.) and level and path and vertex	USPAT	2003/08/12 14:09
-	0	((345/419-428).CCLS.) and (mesh or polygon\$4).ab.) and path near (face or facet or patch)	USPAT	2003/08/12 14:09
-	10	((345/419-428).CCLS.) and (mesh or polygon\$4).ab.) and base near face	USPAT	2003/08/12 14:10
-	42	base with subdivid\$5 with level	USPAT	2003/08/12 14:11
-	0	base with subdivid\$5 with level with (polygon or mesh) with face	USPAT	2003/08/12 14:11
-	5	base with subdivid\$5 with level and polygon	USPAT	2003/08/12 14:12
-	4	unique near (face or patch) near identif\$6	USPAT	2003/08/12 14:12
-	5	unique near (face or patch) near (name or identif\$6)	USPAT	2003/08/12 14:12